

BLUETOOTH DOC	Date / Year-Month-Day 2002-03-27	Approved Draft	Revision 0.95b	Document No
Prepared Bluetooth Audio Video Working Group	e-mail address bt-av-feedback@bluetooth.org			N.B. Confidential

GENERIC AUDIO/VIDEO DISTRIBUTION PROFILE

Abstract

This profile defines the requirements for Bluetooth™ devices necessary to set up streaming channels used for support of audio/video distribution. The requirements are expressed in terms of services provided to applications, and by defining the features and procedures that are required for interoperability between Bluetooth devices in the Audio/Video Distribution usage model.

Revision History

Revision	Date	Comments
0.5	April 2001	Release to Associates
0.7	June 2001	Release to Associates
0.9	September 2001	Release to Associates and Early Adopters
Draft 0.95	October 2001	Release to Associates and Early Adopters
Draft 0.95a	February 11, 2002	Release to Associates and Early Adopters, small clarifications based on IOP and feedback.
Draft 0.95b	March 2002	Release after Adoption Review

Contributors

Morgan Lindqvist	Ericsson
Tsuyoshi Okada	Matsushita Electric Industrial
Kalervo Kontola	Nokia
Vesa Lunden	Nokia
Jurgen Schnitzler	Nokia
Shaun Barrett	Philips
Christian Bouffieux	Philips
Frans de Bont	Philips
Rob J. Davies	Philips
Geert Knapen	Philips
Emmanuel Mellery	Philips
Masakazu Hattori	Sony
Harumi Kawamura	Sony
Rudiger Mosig	Sony
Yoshiyuki Nezu (Owner)	Sony
Hiroyasu Noguchi (Co-owner)	Sony
Tomoko Tanaka	Sony
Junko Ami	Toshiba
Takeshi Saito	Toshiba
Yoshiaki Takabatake	Toshiba
Ichiro Tomoda	Toshiba
Junichi Yoshizawa	Toshiba

Disclaimer and Copyright Notice

The copyright in these specifications is owned by the Promoter Members of Bluetooth SIG, Inc. ("Bluetooth SIG"). Use of these specifications and any related intellectual property (collectively, the "Specification"), is governed by the Promoters Membership Agreement among the Promoter Members and Bluetooth SIG (the "Promoters Agreement"), certain membership agreements between Bluetooth SIG and its Adopter and Associate Members (the Membership Agreements") and the Bluetooth Specification Early Adopters Agreements ("1.2 Early Adopters Agreements") among Early Adopter members of the unincorporated Bluetooth special interest group and the Promoter Members (the "Early Adopters Agreement"). Certain rights and obligations of the Promoter Members under the Early Adopters Agreements have been assigned to Bluetooth SIG by the Promoter Members.

Use of the Specification by anyone who is not a member of Bluetooth SIG or a party to an Early Adopters Agreement (each such person or party, a "Member"), is prohibited. The legal rights and obligations of each Member are governed by their applicable Membership Agreement, Early Adopters Agreement or Promoters Agreement. No license, express or implied, by estoppel or otherwise, to any intellectual property rights are granted herein.

Any use of the Specification not in compliance with the terms of the applicable Membership Agreement, Early Adopters Agreement or Promoters Agreement is prohibited and any such prohibited use may result in termination of the applicable Membership Agreement or Early Adopters Agreement and other liability permitted by the applicable agreement or by applicable law to Bluetooth SIG or any of its members for patent, copyright and/or trademark infringement.

THE SPECIFICATION IS PROVIDED "AS IS" WITH NO WARRANTIES WHATSOEVER, INCLUDING ANY WARRANTY OF MERCHANTABILITY, NONINFRINGEMENT, FITNESS FOR ANY PARTICULAR PURPOSE, SATISFACTORY QUALITY, OR REASONABLE SKILL OR CARE, OR ANY WARRANTY ARISING OUT OF ANY COURSE OF DEALING, USAGE, TRADE PRACTICE, PROPOSAL, SPECIFICATION OR SAMPLE.

Each Member hereby acknowledges that products equipped with the Bluetooth™ technology ("Bluetooth™ Products") may be subject to various regulatory controls under the laws and regulations of various governments worldwide. Such laws and regulatory controls may govern, among other things, the combination, operation, use, implementation and distribution of Bluetooth™ Products. Examples of such laws and regulatory controls include, but are not limited to, airline regulatory controls, telecommunications regulations, technology transfer controls and health and safety regulations. Each Member is solely responsible for the compliance by their Bluetooth™ Products with any such laws and regulations and for obtaining any and all required authorizations, permits, or licenses for their Bluetooth™ Products related to such regulations within the applicable jurisdictions. Each Member acknowledges that nothing in the Specification provides any information or assistance in connection with securing such compliance, authorizations or licenses. NOTHING IN THE SPECIFICATION CREATES ANY WARRANTIES, EITHER EXPRESS OR IMPLIED, REGARDING SUCH LAWS OR REGULATIONS.

ALL LIABILITY, INCLUDING LIABILITY FOR INFRINGEMENT OF ANY INTELLECTUAL PROPERTY RIGHTS OR FOR NONCOMPLIANCE WITH LAWS, RELATING TO USE OF THE SPECIFICATION IS EXPRESSLY DISCLAIMED. BY USE OF THE SPECIFICATION, EACH MEMBER EXPRESSLY WAIVES ANY CLAIM AGAINST BLUETOOTH SIG AND ITS PROMOTER MEMBERS RELATED TO USE OF THE SPECIFICATION.

Bluetooth SIG reserves the right to adopt any changes or alterations to the Specification as it deems necessary or appropriate and to adopt a process for adding new Bluetooth™ profiles after the release of the Specification.

Document Terminology

The Bluetooth SIG has adopted Section 13.1 of the IEEE Standards Style Manual, which dictates use of the words ``shall'', ``should'', ``may'', and ``can'' in the development of documentation, as follows:

- The word *shall* is used to indicate mandatory requirements strictly to be followed in order to conform to the standard and from which no deviation is permitted (*shall* equals *is required to*).
- The use of the word *must* is deprecated and shall not be used when stating mandatory requirements; *must* is used only to describe unavoidable situations.
- The use of the word *will* is deprecated and shall not be used when stating mandatory requirements; *will* is only used in statements of fact.
- The word *should* is used to indicate that among several possibilities one is recommended as particularly suitable, without mentioning or excluding others; or that a certain course of action is preferred but not necessarily required; or that (in the negative form) a certain course of action is deprecated but not prohibited (*should* equals *is recommended that*).
- The word *may* is used to indicate a course of action permissible within the limits of the standard (*may* equals *is permitted*).

The word *can* is used for statements of possibility and capability, whether material, physical, or causal (*can* equals *is able to*).

Contents

1	Introduction	8
1.1	Scope	8
1.2	Profile Dependency	8
1.3	Symbols and Conventions	9
1.3.1	Requirement Status Symbols	9
1.3.2	Signalling Diagram Conventions	9
1.3.3	Notation for Timers	10
2	Profile Overview	11
2.1	Profile Stack	11
2.2	Configurations and Roles	11
2.3	User Requirements and Scenarios	12
2.4	Profile Fundamentals	12
2.5	Conformance	12
3	Application Layer	14
4	AVDTP Interoperability Requirements	15
4.1	Signalling Procedures	15
4.1.1	Connection Establishment	15
4.1.2	Start Streaming	17
4.1.3	Connection Release	17
4.1.4	Suspend	18
4.1.5	Change Parameters	18
4.1.6	Signalling control	19
4.1.7	Security Control	19
4.1.8	AVDTP Signalling Procedures Overview	20
4.2	Transport Services	20
4.3	Error codes	21
5	L2CAP Procedures	22
5.1	Channel Types	22
5.2	Signalling	22
5.3	Configuration Options	22
5.3.1	Maximum Transmission Unit	22
5.3.2	Reliability	23
5.3.3	Quality of Service	23
6	Link Manager (LM) Procedures	24
7	Link Controller (LC) Procedures	25
8	Generic Access Profile Interoperability Requirements	26

8.1	Modes	26
8.2	Security Aspects	26
8.3	Idle Mode Procedures	26
9	Timers	27
10	Testing	28
11	References	29
12	List of Figures	30
13	List of Tables	31
14	Appendix A (Informative): Signalling Flows	32
14.1	Definitions	32
14.2	Streaming Set up and Release	32
14.3	Streaming Suspend and Resume	34
15	Appendix B: Acronyms and Abbreviations	35

1 Introduction

1.1 Scope

The Generic Audio/Video Distribution Profile (GAVDP) defines a generic part of the protocols and procedures that realize distribution of audio content and/or video content using ACL channels. The profile specifies signalling transaction procedures between two devices to set up, terminate and reconfigure streaming channels. Streaming parameters and encode/decode features are included in Advanced Audio Distribution Profile[1] and Video Distribution Profile that depend on this profile. It is not allowed to use the Generic Audio/Video Distribution Profile alone; it is required to use GAVDP in combination with profiles that depend on this profile.

1.2 Profile Dependency

In Figure 1-1 the structure and the dependencies of the profiles are depicted. A profile is dependent upon another profile if it re-uses parts of that profile, by implicitly or explicitly referencing it. Dependency is illustrated in the figure. A profile has dependencies on the profile(s) in which it is contained – directly and indirectly. As indicated in the figure, the Generic Audio/Video Distribution profile is dependent only upon the Generic Access Profile[2]. The terminology, user interface and security aspects, modes and procedures as defined in the Generic Access Profile are applicable to this profile, unless explicitly stated otherwise.




Figure 1-1: Profile Dependency

1.3 Symbols and Conventions

1.3.1 Requirement Status Symbols

In this document the following symbols are used:

‘M’ for mandatory to support (used for capabilities that shall be used in the profile).

‘O’ for optional to support (used for capabilities that may be used in the profile).

‘C’ for conditional support (used for capabilities that shall be used in case a certain other capability is supported).

‘X’ for excluded (used for capabilities that may be supported by the unit, but that shall never be used in the profile).

‘N/A’ for not applicable (in the given context it is impossible to use this capability).

Some excluded capabilities are capabilities that, according to the relevant Bluetooth specification, are mandatory. These are features that may degrade operation of devices following the GAVDP. Therefore, these features shall never be activated while a unit is operating as a unit within this profile.

1.3.2 Signalling Diagram Conventions

In this profile, protocol signals are exchanged by initiating procedures in communicating devices and by exchanging messages. Signalling diagrams use the conventions of Figure 1-2 below. A and B represent devices playing a specific role as defined in Section 2.2.

Specific arrow styles are used in the diagrams to indicate the relevant procedures initiated by the participant devices and the exchanged messages. The STATE of two devices is also expressed in the diagrams.




Figure 1-2: Signalling Conventions

1.3.3 Notation for Timers

Bluetooth timer is introduced in this profile. To distinguish them from timers used in other parts of the specification, these timers are named according to the following convention:

- “T_{GAVDP}nnn” for timers

2 Profile Overview

2.1 Profile Stack

Figure 2-1 shows the protocols used in this profile.




Figure 2-1: Protocol Model

The Baseband[3], LMP[4], L2CAP[5], and SDP[6] are Bluetooth protocols defined in the Bluetooth Core specifications. AVDTP[7] consists of a signalling entity for negotiation of streaming parameters and a transport entity that handles the streaming. For reference, see Chapter 2 and Chapter 5 of AVDTP[7].

2.2 Configurations and Roles

The following roles are defined for devices that implement this profile:

Initiator (INT) – This is the device that initiates a signalling procedure.

Acceptor (ACP) – This is the device that shall respond to an incoming request from the INT.

Note that the roles are not fixed to the devices. The roles are determined when the user initiates a signalling procedure defined in Section 4.1, and they are released when the procedure ends. The roles can be switched between two devices when a new procedure is initiated.

An example of configurations illustrating the roles for this profile is depicted in Figure 2-2.




Figure 2-2: Examples of Configuration

In Figure 2-2, a portable player is the **INT** and headphones are the **ACP**. The **INT** sends signalling messages, for example, to request the establishment of a connection, or control the stream. In the first example the **ACP** shall respond to an incoming stream establishment request from the **INT**. In the second case the **ACP** shall provide the information such as services and transport capabilities it supports.

Note again that the roles can be switched: the portable player can become the **ACP** while the headphones behave as the **INT**. It depends on profile, application and implementation.

2.3 User Requirements and Scenarios

The following scenarios are covered by this profile:

- Set up two devices for A/V data streaming that flows from one end to another, and then connect these devices with Bluetooth transaction.
- Control the established streaming.

2.4 Profile Fundamentals

This profile is based on Bluetooth v.1.1 specification. Here is a brief summary of the interactions that take place when the **INT** wishes to send messages to the **ACP**.

- A link shall be established before a signalling session starts.
- There are no fixed master/slave roles.
- Use of security features in link level such as authorisation, authentication and encryption are optional. Support for authentication and encryption is mandatory, such that the device can take part in the corresponding procedures if requested from a peer device.

2.5 Conformance

When conformance to this profile is claimed, all capabilities indicated mandatory for this profile shall be supported in the specified manner (process mandatory). This also

applies for optional and conditional capabilities for which support is indicated. All mandatory, optional, and conditional capabilities, for which support is indicated, are subject to verification as part of the Bluetooth certification program.

3 Application Layer

This section describes the feature requirements on units complying with the GAVDP. There is no fixed **INT/ACP** role for the devices.

Table 3-1 shows the feature requirements for this profile.

Item No.	Feature	Support in INT*	Support in ACP**
1	Connection	M	M
2	Transfer Control	O	O
3	Signalling Control	M	M
4	Security Control	O	O
* The mandatory and optional requirements only applies on the initiator part of the procedure.			
** The mandatory and optional requirements only applies on the acceptor part of the procedure.			

Table 3-1: Application Layer Features

Table 3-2 maps each feature to the procedures used for that feature, and shows whether the procedure is optional or mandatory for that feature. The procedures are described in the referenced section.

Item No.	Feature	Procedure	Ref.	Support in INT*	Support in ACP**
1	Connection	Connection Establishment	4.1.1	M	M
		Start Streaming	4.1.2	M	M
		Connection Release	4.1.3	M	M
2	Transfer Control	Suspend	4.1.4	O	O
		Change Parameters	4.1.5	O	O
3	Signalling Control	Abort	4.1.6	M	M
4	Security Control	Security Control	4.1.7	O	O
* The mandatory and optional requirements only applies on the initiator part of the procedure.					
** The mandatory and optional requirements only applies on the acceptor part of the procedure.					

Table 3-2: Application Layer Feature to Procedure Mapping

4 AVDTP Interoperability Requirements

4.1 Signalling Procedures

The interoperability requirements for the signalling entity are contained in this section.

In use of AVDTP the following three states are exposed to the users of GAVDP:

- <IDLE>: The initial state where no streaming connection has been established, while L2CAP channel for signalling is already open.
- <OPEN>: The streaming connection has been established between two devices.
- <STREAMING>: Both devices are ready for streaming.

Figure 4-1 shows the possible transitions. *Security Control* procedure in Section 4.1.7 can be executed in <OPEN> and <STREAMING> and does not result in a state change. For more details, see Section 6.3 and Chapter 8 of AVDTP[7].




Figure 4-1: Signalling Procedures

4.1.1 Connection Establishment

This procedure shall be used when a device wishes to establish a streaming connection with the other device. Prior to initiating this procedure, an L2CAP channel for signalling shall be established as described in Section 6.1 of AVDTP[7]. The initial state of the both devices is <IDLE>.

Then, the **INT** shall initiate *Stream Endpoint (SEP) Discovery* procedure of AVDTP if the **INT** has not collected SEP information before, or wishes to refresh it.

Then, *Get Capabilities* procedure of AVDTP should be initiated to collect service capabilities of the **ACP** using the SEP information. This procedure does not have to be executed when the **INT** already knows the services provided by the **ACP**.

Based on collected SEP information and service capabilities, the **INT** shall select specific services and configure the **ACP** by using the *Stream Configuration* procedure defined in AVDTP. Then, L2CAP channels are established as defined in the *Stream Establishment* procedure in AVDTP. Finally, the states of both devices are set at <OPEN>, and the **INT/ACP** roles are released after the procedure.

Note: If the L2CAP channel establishment has failed after the Open Stream Command of AVDTP, it is recommended to perform the Abort Command of AVDTP to get both **ACT** and **INT** synchronised.

To start a stream, the *Start Streaming* procedure in Section 4.1.2 shall be initiated to confirm if both devices are ready for streaming and change the state from <OPEN> to <STREAMING> as defined in Section 6.5 of AVDTP[7].




Figure 4-2: Connection Establishment

4.1.2 Start Streaming

When the device wishes to start or resume the A/V streaming, this procedure shall be initiated to change the state from <OPEN> to <STREAMING> as defined in Section 6.5 of AVDTP[7].

The **INT** initiates *Start Streaming* procedure of AVDTP by a user initiated action or an internal event. The streaming shall be started/resumed after this procedure.




Figure 4-3: Start Streaming

4.1.3 Connection Release

The **INT** initiates the *Stream Release* procedure of AVDTP to release L2CAP channels for streaming. This procedure may be initiated both from <OPEN> and <STREAMING>, and set the state at <IDLE> for both devices.

The L2CAP channel for signalling may be released after this procedure, if necessary.




Figure 4-4: Connection Release

4.1.4 Suspend

When the device wishes to suspend the A/V streaming, the procedure shall be initiated to change the state from <STREAMING> to <OPEN>.

The **INT** initiates *Stream Suspend* procedure of AVDTP by a user initiated action or an internal event. The streaming shall be suspended after the procedure.




Figure 4-5: Suspend

4.1.5 Change Parameters

In order to change the application service parameters, both devices shall be in <OPEN> state. If the state is <STREAMING> the *Suspend* procedure in Section 4.1.4 shall be executed beforehand to suspend the stream and change the state to <OPEN> for both devices.

The procedure is initiated by a user action or an internal event. If the **INT** has not obtained service capability information of the **ACP** by then, the *Get Capabilities* procedure of AVDTP is executed first. Then, the **INT** selects and specifies new parameters according to the information and requests the **ACP** to reconfigure these parameters with the *Stream Reconfigure* procedure of AVDTP.

After closing this procedure, the state of the devices remains <OPEN>. It is necessary to initiate *Start Streaming* procedure defined in Section 4.1.2 to resume the stream.




Figure 4-6: Change Parameters

4.1.6 Signalling control

This procedure may be used to recover from a loss of a signalling message, which could result in inconsistency of the **INT** and the **ACP**. For more details, see Section 9.11 of AVDTP[7].




Figure 4-7: Signalling control

4.1.7 Security Control

This procedure shall be used to exchange security control messages between the **INT** and the **ACP**.




Figure 4-8: Security Control

4.1.8 AVDTP Signalling Procedures Overview

This section defines the required AVDTP signalling procedures in the Generic Audio/Video Distribution profile. Details of procedures and signalling messages are fully described in Chapter 6, 8 and 9 of AVDTP[7].

Item No.	Capability	Support in INT*	Support in ACP**	T _{GA} VD _P 100 applies
1	Stream End Point Discovery	M	M	No
2	Get Capabilities	M	M	No
3	Stream Configuration	M	M	Yes
4	Stream Establishment	M	M	Yes
5	Stream Start	M	M	Yes
6	Stream Release	M	M	Yes
7	Stream Suspend	O	O	Yes
8	Stream Reconfigure	O	O	Yes
9	Fragmentation	M	M	No
10	General Reject	N/A	M	No
11	Abort	M	M	Yes
12	Security Control	O	O	No

* The mandatory and optional requirements only applies on the initiator part of the procedure.
 ** The mandatory and optional requirements only applies on the acceptor part of the procedure.

Table 4-1: AVDTP Signalling Capabilities

4.2 Transport Services

Once a stream connection is established between the **INT** and the **ACP**, the devices are ready to transport A/V data. AVDTP provides several transport services related to basic transport, quality of service and manipulation of transport packets for efficient use of the bandwidth. These transport services are fully described in Section 5.4 and Chapter 7 of AVDTP[7].

The necessity of these transport services depends on applications. The requirement of these services is described in the application profiles such as Advanced Audio Distribution Profile[1].

4.3 Error codes

Table 4-2 defines an 8-bits ERROR_CODE field that is transported over the air in signalling response messages when an ACP device rejects a signalling command message received from a distant INT device. The ERROR_CODE field received from an ACP device is exposed to the INT application through the AVDTP service interface. The range 0xC0-0xFF is reserved for the profile residing on top GAVDP.

Error ID	Related Signalling command	Error Abbreviation	Error Description
0x80	Set Configuration	BAD_SERVICE	The service category stated is invalid.
0x81	Set Configuration	INSUFFICIENT_RESOURCE	Lack of resource new Stream Context.

Table 4-2: ACP-Upper Layer to INT-AVDTP Signal Response Error Codes

5 L2CAP Procedures

The following text together with the associated sub-clauses defines the mandatory requirements with regard to this profile.

	Procedure	Support
1.	Channel types	
	Connection-oriented channel	M
	Connectionless channel	X1
2.	Signalling	
	Connection establishment	M
	Configuration	M
	Connection Termination	M
	Echo	M
	Command Rejection	M
3.	Configuration Parameter Options	
	Maximum Transmission Unit	M
	Flush Timeout	M
	Quality of Service	O
X1: Connectionless channel is not used within the execution of this profile, but concurrent use by other profiles/applications is not excluded.		

Table 5-1: L2CAP Capabilities

5.1 Channel Types

In this profile, only connection-oriented channels shall be used. This implies that broadcasts shall not be used in this profile.

The AVDTP PSM value is used in the L2CAP connection request. See the Bluetooth Assigned Numbers[8] for the AVDTP PSM.

5.2 Signalling

Only the **INT** issues an L2CAP Connection Request within the execution of *Connection Establishment* procedure in this profile. (See Section 4.1.1) The GAVDP does not impose any additional restrictions or requirements on L2CAP signalling.

5.3 Configuration Options

This section describes the usage of the configuration options in this profile.

5.3.1 Maximum Transmission Unit

The minimum MTU that a L2CAP implementation for this profile shall support is 48 bytes.

5.3.2 Reliability

The flush timeout value shall be defined in the profiles dependent on GAVDP.

5.3.3 Quality of Service

Negotiation of Quality of Service is optional in this profile.

6 Link Manager (LM) Procedures

The procedure for SCO links is excluded in this profile. Except for this, there is no change to the requirements as stated in the Link Manager specification itself.

7 Link Controller (LC) Procedures

The following table lists all features at LC level, and the extra requirements are added to the one in the Baseband specification by this profile.

	Procedure	Support in INT	Support in ACP
1.	Inquiry	M	X
2.	Inquiry scan	X	M
3.	Paging	M	X
4.	Page scan		
	A. Type R0	X	C1
	B. Type R1	X	C1
	C. Type R2	X	C1
5.	Packet types		
	A. ID packet	M	M
	B. NULL packet	M	M
	C. POLL packet	M	M
	D. FHS packet	M	M
	E. DM1 packet	M	M
	F. DH1 packet	M	M
	G. DM3 packet	O	O
	H. DH3 packet	O	O
	I. DM5 packet	O	O
	J. DH5 packet	O	O
	K. AUX packet	X	X
	L. HV1 packet	X	X
	M. HV2 packet	X	X
	N. HV3 packet	X	X
	O. DV packet	X	X
6.	Inter-piconet capabilities	X	X
7.	Voice codec		
	A. A-law	X	X
	B. μ -law	X	X
	C. CVSD	X	X
	D. Transparent Data	X	X

C1: it is mandatory to implement at least one of the page scan modes.

Table 7-1: LC Capabilities

8 Generic Access Profile Interoperability Requirements

The GAVDP requires compliance to the Generic Access Profile. This section defines the support requirements for the capabilities as defined in the Generic Access Profile.

8.1 Modes

The table shows the support status for Modes within this profile.

	Procedure	Support in INT	Support in ACP
1.	Discoverability modes		
	Non-Discoverable mode	X	C1
	Limited discoverable mode	X	O
	General discoverable mode	X	M
2.	Connectability modes		
	Non-Connectable mode	X	X
	Connectable mode	M	M
3.	Pairing modes		
	Non-pairable mode	O	O
	Pairable mode	C2	C2
C1: If limited discoverable mode is supported, non-discoverable mode is mandatory, otherwise optional.			
C2: If bonding is supported, pairable mode is mandatory, otherwise optional.			

Table 8-1: Modes

8.2 Security Aspects

There is no change to the requirements as stated in the Generic Access Profile.

8.3 Idle Mode Procedures

The table shows the support status for Idle mode procedures within this profile.

	Procedure	Support in INT	Support in ACP
1.	General inquiry	M	X
2.	Limited inquiry	O	X
3.	Name discovery	O	X
4.	Device discovery	O	X
5.	Bonding	O*	O*
* Whenever supported, the INT <u>shall</u> at least support initiation of bonding, and the ACP at least acceptance of bonding.			

Table 8-2: Supported Idle Mode Procedures

9 Timers

The following timers are required by GAVDP.

Timer name	Proposed value	Description	Comments
T _{GAVDP} 100	0.5~3.0 Seconds	Signalling transaction timer	

Table 9-1: Timers

10 Testing

Tested functionality is defined in [9].

11 References

- [1] Bluetooth SIG, Specification of the Bluetooth System, Profiles, Version 1.0, Advanced Audio Distribution Profile
- [2] Bluetooth SIG, Specification of the Bluetooth System, Profiles, Version 1.1, Part K:1 (Generic Access Profile)
- [3] Bluetooth SIG, Specification of the Bluetooth System, Core, Version 1.1, Part B (Baseband)
- [4] Bluetooth SIG, Specification of the Bluetooth System, Core, Version 1.1, Part C (LMP)
- [5] Bluetooth SIG, Specification of the Bluetooth System, Core, Version 1.1, Part D (L2CAP)
- [6] Bluetooth SIG, Specification of the Bluetooth System, Core, Version 1.1, Part E (SDP)
- [7] Bluetooth SIG, Specification of the Bluetooth System, Core, Version 1.0, Audio/Video Distribution Transport Protocol Specification
- [8] Bluetooth SIG, Bluetooth Assigned Numbers,
<http://www.bluetooth.org/assigned-numbers.htm>
- [9] Bluetooth SIG, Specification of the Bluetooth System, ICS, Version 1.0, Profile ICS proforma for the Generic Audio/Video Distribution Profile

12 List of Figures

Figure 1-1: Profile Dependency	9
Figure 1-2: Signalling Conventions	10
Figure 2-1: Protocol Model.....	11
Figure 2-2: Examples of Configuration	12
Figure 4-1: Signalling Procedures.....	15
Figure 4-2: Connection Establishment.....	16
Figure 4-3: Start Streaming.....	17
Figure 4-4: Connection Release	17
Figure 4-5: Suspend.....	18
Figure 4-6: Change Parameters.....	19
Figure 4-7: Signalling control	19
Figure 4-8: Security Control	20
Figure 14-1: Streaming setup and release.....	33
Figure 14-2: Streaming suspend and resume.....	34

13 List of Tables

Table 3-1: Application Layer Features	14
Table 4-1: AVDTP Signalling Capabilities.....	20
Table 4-2: ACP-Upper Layer to INT-AVDTP Signal Response Error Codes	21
Table 5-1: L2CAP Capabilities.....	22
Table 7-1: LC Capabilities.....	25
Table 8-1: Modes	26
Table 8-2: Supported Idle Mode Procedures.....	26
Table 9-1: Timers	27

14 Appendix A (Informative): Signalling Flows

This appendix contains a typical combination of signalling procedures defined in this profile. This appendix is informative only. The diagrams do not represent all possible combination of signalling flows as defined by this profile.

14.1 Definitions

In this appendix the **SRC** and the **SNK** are used for the role of devices to clarify the flow of procedures in the actual device implementation. The **SRC (SNK)** is the device that can send (receive) A/V streaming data. For reference, see Section 2.2 in Advanced Audio Distribution Profile[1].

In the following diagrams the **SRC** is assumed to be the **INT**, while the **SNK** to be the **ACP**. However, the **INT/ACP** roles are flexible; for example, it is possible that the **SRC** initiates the *Connection Establishment* procedure, followed by a *Start Streaming* procedure initiated by the **SNK**. It depends on the implementation.

The diagrams contain procedures defined in different profiles. <procedure> , <procedure*>, and <procedure**> indicate GAVDP, GAP[2] and SDP[6] procedures, respectively.

14.2 Streaming Set up and Release

Figure 14-1 shows an example of signalling flows covering the initial device discovery, service discovery, and streaming connection establishment. The diagram fully contains a series of procedures necessary to set up and release the streaming connection defined in this profile.




Figure 14-1: Streaming setup and release

14.3 Streaming Suspend and Resume

Figure 14-2 shows a series of procedures used to suspend the streaming or change streaming parameters.




Figure 14-2: Streaming suspend and resume

15 Appendix B: Acronyms and Abbreviations

Acronym	Description
AV	Audio/Video
ACP	Acceptor
AVDTP	Audio/Video Distribution Transport Protocol
GAP	Generic Access Profile
GAVDP	Generic Audio/Video Distribution Profile
ICS	Implementation Conformance Statement
INT	Initiator
LC	Link Controller
MTU	Maximum Transmission Unit
PSM	Protocol/Service Multiplexer
SDP	Service Discovery Protocol
SEP	Stream End Point
SNK	Sink
SRC	Source