

IT-SDS-302-T-2D (RS-232)

2-Ports RS-232 to Ethernet Serial Server

Features

- ◎ Support 10/100M Ethernet
- ◎ Support 2 Ports RS-232
- ◎ Support WEB and Telnet configuration
- ◎ Support TCP, UDP, ARP, ICMP, DHCP and DNS protocol
- ◎ Support TCP Server, TCP Client, TCP Auto, UDP and Real COM driver working mode
- ◎ Support UDP multicast and UDP subnet mode
- ◎ Support heartbeat time and time over disconnect function
- ◎ Support cross-gateway and cross-router communication
- ◎ Support virtual serial COM port access and Network interruption automatic recovery
- ◎ Provide Windows configuration tools for easy to use, easy to bath install.
- ◎ Industrial grade design, IP30 protection grade
- ◎ No fan, low consumption design
- ◎ Working temperature: -40~85°C



1

Introduction

IT-SDS-302-T-2D (RS-232) is an high performance, industrial grade serial to Ethernet server, it can satisfy some kinds of customer requirements in consumption, temperature, volume and handle ability. It provides 2 ports RS232 (RS-232 connector: RJ45) and 1 port 10/100Base-Tx Ethernet, can focus manage disperse serial device, master through network, easy, convenience. In application, can configure, upgrade through WEB.


Moreover, IT-SDS-302-T-2D (RS-232) provide strong function

configuration tools based in Windows platform, it can guide user configure the device step by step, all configurations are coming true by WEB or Telnet, support cross-gateway and cross-router, user can flexible configure IP address, server and client mode, data bag size etc.

IT-SDS-302-T-2D (RS-232) adopts EMC protection design, can work in rugged environment.

Dimensions

Unit (mm)



Specifications

Ethernet ports

Standard: 10Base-T, 100Base-TX

Protocol: Support TCP, UDP, APR, ICMP and DHCP

Signal: Rx+, Rx-, Tx+, Tx-

Speed: 10/100Mbps

Working: Full-duplex and half duplex

Working mode: Support TCP Server and Client

Transfer distance: 100m

Connector: RJ45

RS232 ports

RS232 port number: 2

RS-232 signal: DCD, RXD, TXD, DTR, GND, DSR, RTS, CTS

Parity bit: None, Even, Odd, Space, Mark

Data bit: 5bit, 6bit, 7bit, 8bit

Stop bit: 1bit, 2bit

Band rate: 300bps~115200bps

Loading: point to point

Transfer distance: no more than 15m

Connector: RJ45

Protection: class 3 static

LED Indicators

Power (PWR)

Ethernet port connect statue (Link)

RS232 port data indicator: TX, RX

Power requirements

Input voltage: 9~48VDC

No-load consumption: 0.66W @ 12VDC

Full-load consumption: 0.67W @ 12VDC

Environment limits

Working temperature: -40~85°C

Storage temperature: -40~85°C

Relative humidity: 5%~95% (non-condensing)

Mechanical

Shell: IP30 protection, metal shell

Installation: Wall mounting

Weight: 227g

Size (L×W×H): 100mm×69mm×22mm

Standards

EMS: EN 61000-4-2 (ESD) Level 3,

Shock: IEC 60068-2-27

Free fall: IEC 60068-2-32

Vibration: IEC 60068-2-6

Warranty

Warranty time: 5 years

Certificates

CE, FCC, RoHS, UL508 (pending)

Ordering Informations**IT-SDS-302-T-2D (RS-232)-P (9~48VDC)** 2-ports RS232 to Ethernet (10M/100M), DC9~48V, wall mounting**Packing List**

1. IT-SDS-302-T-2D (RS-232)×1
2. User manual ×1
3. Straight network cable ×1
4. Power adapter ×1
5. CD ×1
6. Warranty card ×1
7. Certificate of quality×1

Optional accessories:

DIN-Rail Mounting Kit (35mm) ×1