

# IT-232P33-TTL

RS-232 to 3.3V TTL Converter (DB9)

## Features

1. Port Powered: no external power is necessary
2. Data Direction, auto-turnaround, no flow control is necessary
3. Plug-and-Play (Device is hot-pluggable)
4. Built-in surge protection, static protection and circuit protection



## Introduction

The Intellisystem IT-232P33-TTL is a bi-directional port powered RS-232 to 3.3V TTL converter in a 9 pin format. It can convert any standard full duplex RS-232C port to a 3.3V TTL signal and vice versa. The unit is powered from the RS-232 data lines. It also supports data direction auto-turnaround. Therefore, no external power or flow control is required. The data direction auto-turnaround

automatically enables the TTL driver when data is present on the RS-232 side making the device plug-and-play, requiring no software drivers. The IT-232P33-TTL has a DB9 female connector on the RS-232 side and either a DB9 male connector or 5-way terminal block on the TTL side. Separate terminal block is included in package.

## Specification

Standards: EIA RS-232C standard

RS-232 signal: TX, RX, GND

TTL signal: IN, OUT, GND

Baud rate: 300~115200bps

Transfer distance: 3.3V TTL side: 3m

RS-232 side: no less than 5m

Connectors: RS-232 Side: DB9 Female and

3.3V TTL Side: DB9 Male or 5 bit Terminal Block

Port protect: 600W surge protection, 15KV ESD protection

### Power

Power: Port powered from RS-232 data lines

Current consumption: Less than 10mA

### Environment

Operating temperature: -10°C to 60°C

Storage temperature: -40°C to 85°C

Humidity: 5% to 95% (no condensation)

### Appearance

Dimensions: 62.8mm×33.8mm×17.8mm

80.3mm×33.4mm×18.6mm (with terminal block)

Material: Iron (shell)


Weight: 24g (with terminal block: 36g)

**Warranty: 5 years**

**Approvals: FCC, CE, RoHS approvals**

## Packing List

1. IT-232P33-TTL ×1
2. Separate terminal block (DB9F to 5 bit) ×1
3. User manual ×1



HOST/PC/DTE

