

FMA-180



TECHNICAL SPECIFICATIONS

The iNetVu® 180 Fixed Motorised Antenna system is a self-pointing auto-acquire unit that can be mounted as a permanent installation. Works seamlessly with the auto-pointing iNetVu® 7024 Controller.



Features

- 1.8m Offset, prime focus, glass fibre SMC reflector
- Designed to work with the iNetVu® 7024 Controller
- Works seamlessly with the world's most popular commercially available satellite modems
- 2 Axis motorization, 3rd Axis (Polarization) optional
- Supports manual control when required
- It is a cost effective solution for multi-satellite communication at any location
- One button, auto-pointing controller acquires any Ku or C band satellite within 2 minutes
- Locates satellites using the most advanced satellite acquisition methods
- Eliminates costly repointing and network downtime due to inadvertent motion, satellite change, areas where ground shifts occur (earthquakes, landslides, mine blast zones, etc...)
- Can be easily relocated when mounted on a semi-permanent platform without the need for any specialised equipment
- Any compatible fixed installation can be easily converted and upgraded to a fully motorised system
- Supports Prodelin 1.8m antenna, Model 1184
- System designed for 4W and higher BUCs. 10 kg (Max.) weight for RF electronics (BUC and LNB)
- 1Year Warranty

Application Versatility

The FMA-180 system is easily configured to provide instant access to satellite communications for any application that requires reliable and/or remote connectivity in a rugged environment. Ideally suited for industries such as Oil & Gas Exploration, Mining, Disaster Management, Construction, Mobile Offices and Emergency Services.

www.intellisystem.it

Via Augusto Murri N°1 - 96100 Siracusa (ITALY)
info@intellisystem.it +39 (0)931-1756256 +39 335 1880035

INTEGRATED SATELLITE SOLUTIONS

Specifications are subject to change

May 2016

FMA-180



TECHNICAL SPECIFICATIONS

Mechanical

Antenna size	1.8m (71")
Reflector Material	Glass reinforced polyester SMC
Platform Type	3 axis Motorized, Galvanized steel
Antenna optics	Prime Focus, offset feed
Mast size	3.5 SCH 40 pipe (4.00" OD)
Elevation range	80° (10° to 90° adjustable)
Azimuth Range	100° - (360° Manual adjustable)
Polarization Range	± 90°

Environmental

Wind loading	
Operational	80 km/h (50mph)
Survival	201 km/h (125mph)
Temperature	
Operational	-30°C to 55°C (-22°F to 130°F)
Survival	-40°C to 65°C (-40°F to 150°F)

Electrical

Elevation Actuator	24V
Azimuth Actuator	24V
Rx & Tx Cables	2 RG6 Cables -15m (50 ft) each
Control Cables	
Standard	15m (50 ft) Ext. Cable
Optional	Up to 100m (330 ft) available

Ku-Band

	Receive	Transmit
Operating Frequency (GHz)	10.95 - 12.75 ⁽¹⁾	13.75 - 14.50
Midband Gain (± .2dB)	45.00	46.50
Antenna Noise Temp. (K)	10° EL= 44 / 40° EL= 33	
Sidelobe Envelope Co-Pol (dBi)		
Mainbeam <Θ<7°	29-25 LogΘ	
7° <Θ< 9.2°	+8	
9.2° <Θ <48°	32-25 LogΘ	
48° <Θ <180°	-10 Ave.	
Cross Polarization	> -30 dB on axis	
Feed Interface	WR 75	WR 75
VSWR	1.3:1 (Max.)	

Note: ⁽¹⁾ LNB PLL Type required with stability better than ± 25 KHz

C-Band (Linear)

	Receive	Transmit
Operating Frequency (GHz)	3.625 - 4.20 ⁽¹⁾	5.85 - 6.425
Midband Gain (± .2dB)	35.50	39.50
Antenna Noise temp.(K)	10° EL= 56 / 40° EL=46	
Sidelobe Envelope Co-Pol (dBi)		
Mainbeam <Θ<7°	29-25 LogΘ	
7° <Θ< 9.2°	+8	
9.2° <Θ <48°	32-25 LogΘ	
48° <Θ <180°	-10 Ave.	
Cross Polarization	> -30 dB on axis	
Feed Interface	CPR 229 F	CPR 137 or type N
VSWR	1.3:1 (Max.)	

C-Band (Circular)

	Receive	Transmit
Operating Frequency (GHz)	3.625 - 4.20 ⁽¹⁾	5.85 - 6.425
Midband Gain (± .2dB)	35.50	39.90
Antenna Noise Temp. (K)	10° EL=30 / 40° EL=20	
Sidelobe Envelope Co-Pol (dBi)		
Mainbeam <Θ<7°	29-25 LogΘ	
7° <Θ< 9.2°	+8	
9.2° <Θ <48°	32-25 LogΘ	
48° <Θ <180°	-10 Ave.	
Feed Interface	CPR 229 F	CPR 137 or type N
VSWR	1.3:1 (Max.)	

Shipping Weights & Dimensions*

Pallet 1: FMA 1.8m Ku or C band System with 3rd axis motorization on skid
157.5 cm x 106.7 cm x 61 cm (62"x42"x24"); 95.3 Kg (210 lbs);
Pallet 2: FMA 1.8m Reflector on skid
208.3 cm x 208.3 cm x 35.6 cm (82"x82"x14"); 80.3 Kg (177 lbs);

**The shipping weights/dims can vary for particular shipments depending on actual system configuration, quantity, packaging materials and special requirements*

www.intellisystem.it

Via Augusto Murri N°1 - 96100 Siracusa (ITALY)
info@intellisystem.it +39 (0)931-1756256 +39 335 1880035

INTEGRATED SATELLITE SOLUTIONS

Specifications are subject to change

May 2016