

3000 Controller



TECHNICAL SPECIFICATIONS



The new iNetVu® 3000C hand-held manual controller has the same look and feel as a video game controller. It allows you to operate the platform without having the auto-pointing controller or PC attached to it. In addition, this controller makes it possible to operate the iNetVu® mobile antenna at variable speeds.

A useful tool for conducting demonstrations, installations, testing or for emergency backup situations.

Features

- Jog control on 3 axis
- Compatible with all iNetVu® Mobile Platforms
- Ability to raise, stow, and move the iNetVu® Mobile Platform during demos, installations, trouble-shooting etc.
- Compact, ergonomic case design
- LCD display for operation and limits status
- 10-speed operation
- Directly attachable to any 12VDC / 24VDC power supply
- Enhanced operation with feedback control
- Standard 2 year warranty

Note: ⁽¹⁾ Required for new iNetVu® 24V based models

⁽²⁾ Required for new iNetVu® 24V based models equipped with 7720 Works with combined PWR/CAN external cable

⁽³⁾ Cables length up to 50ft available

Electrical

Power Input	
3000C-12	12VDC @ 15 Amp (Max.)
3000C-24 ⁽¹⁾	24VDC @ 8 Amp (Max.)
3000C-24-CAN ⁽²⁾	24VDC @ 8 Amp (Max.)
Motor ⁽³⁾	9 pin; 4.5m (15 ft) cable (optional)
Sensor ⁽³⁾	DB-26; 4.5m (15 ft) sensor cable (optional)

Environmental

Operating temperature	-20° to +60° C (-4° to +140° F)
Storage temperature	-40° to +70° C (-40° to +158° F)
Standard	RoHS compliant

Mechanical

Dimensions	W: 8 cm (7") H: 13 cm (5") D: 5 cm (2")
Weight	500 gm (1 lbs)

Shipping Dimensions

56 cm x 51 cm x 13 cm (22" x 20" x 5"), 3.7 kg (8 lbs)

www.intellisystem.it

Via Augusto Murri N°1 - 96100 Siracusa (ITALY)

info@intellisystem.it +39 (0)931-1756256 +39 335 1880035

INTEGRATED SATELLITE SOLUTIONS

Specifications are subject to change

May 2016