

7 inch IP Camera Tester IT-G600-IPC

Applications:

- Analog camera test
- IP camera test, support 4k, H.264 and H.265
- 8MP TVI test, 8MP CVI test, 5MP AHD test
- HD-SDI / EX-SDI test
- Digital Multimeter
- HDMI input and output
- TDR cable open circuit and short circuit measurement
- Optical power meter
- Visual fault locator
- Video level meter for analog camera
- Cable tracer app with toner wand



Features:

- English, Polish, Italian, Spanish, French and other languages menu optional
- 7 inch IPS touch screen,1280*800 resolution
- H.264 and H.265, 4K video display via mainstream
- Rapid video, just by one key to detect all network cameras and auto display
- Built-in WiFi to receive network image and data, create wifi hotspot , support browser
- Rapid onvif, auto log in and display image from the camera, activate Hikvision camera, and also can create testing report
- 8MP TVI test, 3840 x 2160, 15 FPS, 4xzoom, video record and playback ,coaxial PTZ control and call camera OSD menu
- 5MP AHD test, 2592 x 1944P, 12.5/20FPS, 4xzoom, video record and playback, coaxial PTZ control and call camera OSD menu
- 8MP CVI test, 3840 x 2160, 12.5/15 FPS, 4xzoom, video record and playback, coaxial PTZ control and call camera OSD menu
- HD-SDI / EX-SDI camera test, support 1080P 50/60 FPS
- HDMI input, 720x480p / 720x576p / 1280x720p / 1920x1080p / 1024x768p / 1280x1024p / 1280x900p / 1440x900p display image, record and snapshot
- IP and analog cameras testing at the same time, converter test from analog to digital via dual test window IP & CVBS
- CVBS loop test, the tester send and receive color bar generator signal to check BNC cable
- Traffic monitoring of the tester "Lan port", display network port or wifi connection real-time upload and download speeds and other network parameters
- Support user self-install apps, for example install android version apps, like skype, wechat, etc
- 4K video files and MKV / MP4 media files play
- Quick office apps (excel, word, ppt format), can edit the documents
- Screen lock, password lock and pattern lock are optional
- TesterPlay (screen projection): tester, android version mobile phone and PC display at the same time



- Shortcut button, drop-down menu, can select PoE power ,IP setting, wlan switch, HDMI in functions etc in any interface
- Enhanced cable tester, UTP cable, telephone cable as well as other cables' order and connectivity test, testing report can be saved.
- Screen management, Lite mode and normal mode for option, move the function's icons, create new directory, theme and background setting
- Display onvif IP camera image, onvif PTZ controller, IP discovery.
- Support more than 80 customized IP cameras protocols
- Support ip camera apps and RTSP to view IP camera image
- Network bandwidth testing
- FTP Server, Static IP address, DHCP, simultaneously test different segments' IP cameras
- PoE 24W power supply to IP camera
- HDMI signal output, support 1080P
- DC12V 2A power output for camera
- USB 5V 2A power output to mobile phone
- Led Lamp, easy to operate at night
- Micro SD card moveable
- LCD screen brightness/contrast/color saturation adjustable
- Automatically adapts and displays the video format of NTSC/PAL
- Enhanced color bar generator, by receiving the video color bar to test the video channel whether transmit normally
- 4x zoom, video image can be magnified to view the details, easy to use (both for analog and IP video)
- Video record and playback (both for analog and IP video)
- Snapshot and save the current image as JPG file in the SD card (both for analog and IP video)
- Ping testing, test IP camera or other network devices' Ethernet port whether work normally, and the IP address whether right
- IP address scan, quickly search the IP address for the connected IP camera and other network devices
- PoE voltage measurement, test the PoE switch's voltage to IP cameras, wireless AP device and other PD devices
- Device Port flicker, easy to find the connected PoE switch port by sending special signals, the connected PoE port will flicker at special frequency.
- Link monitor; check the setting IP address whether occupied.
- PTZ address scan, search up the ID of PTZ camera.
- Network cable and Telephone cable testing, display the sequence of connection and the No. of the LAN cable. RJ45 cable TDR test
- Support RS485, rate 600 \sim 115200bps adjustable
- Multi-protocol. Supports more than thirty PTZ protocols. Such as Pelco-P, Pelco-D, Samsung etc.
- PTZ protocol analysis, control protocol command displays to check RS485 transmission
- PTZ control. Pan/tilt the PTZ unit, zooms in/out the lens, adjusts the focus, aperture and sets and the preset position
- Audio input test and output, test the audio signal from pickup devices, support audio output
- Digital Multimeter, voltage, current, resistance and capacitance can be tested, continuity testing, diode testing
 Optical power meter, it can measure the optical power value
- Visual fault locator, check fiber optical's breaking, cracking, bending failure etc
- TDR cable open circuit and short circuit measurement cable length and short circuit measurement (BNC cable, network cable etc.)
- PEAK video signal level, SYNC signal level, COLOR BURST chroma level measurement
- Cable tracer app with toner wand, send the specific signal, easy to find out the connected cable from messy cables.
- Lithium Ion Polymer Battery .The device employs advanced power control and protection circuit. The device is high power-efficient, energy saving and environmental protection. It can last 10 hours for normal use after charging for 6 hours



Specification

Model Number	IT-G600-IPC			
Signal System	NTSC / PAL (Auto-Selecting)			
Display	New 7 inch IPS touch screen, 1280*800 resolution			
IP camera type	4K, H.264, H.265, Onvif, Onvif PTZ, ACTi, Dahua IPC-HFW2100P, Hikvision DS-2CD864-E13, Samsung			
	SNZ-5200, Honeywell HICC-2300T, etc. Customized protocols are available			
Rapid Video	Auto view the video, create testing report			
Hikvision test tool	pressing just one key to activate hikvision camera , Image test, can modify the user name, password and IP			
	parameters			
Dahua test tool	Dahua camera test, modify the user name, password and IP parameters			
N	FTP Server, Static IP address, DHCP, simultaneously test different segments' IP cameras, Network			
Network test	bandwidth testing, IP discovery			
ID comoro anno	Support video management software to view IP camera image, such as Hikvision ivms-4500, Dahua			
IP camera apps	gDMSS HD Lite			
RTSP	Support RTSP to view IP camera image			
LCD adjust	Adjustable brightness, contrast, color of LCD			
HDMI input	1 channel HDMI input, support 1080P			
HDMI signal output	1 channel HDMI output, support 1080P			
Network port	10/100/1000M auto adjust, RJ45			
Wifi	Built in Wifi, speeds 150M, receive wireless camera image etc. Create wifi hotspot			
PoE power output	PoE 24W power supply to IP camera			
Video Input / Output	1 channel BNC input & 1 channel BNC looped output			
Video Output Mode	1.0 Vp-p			
CVBS loop test	the tester send and receive color bar generator signal to check BNC cable			
Power Adapter	5V DC, 2A input supply			
Power output	12V DC, 2A power output for camera			
Audio input	1 channel audio signal input to test pickup device, 1 channel audio signal output to connect headphone			
USB power output	USB 5V 2A power output to mobile phone			
Communication	RS485			
Baud Rate	150, 300, 600, 1200, 2400, 4800, 9600, 19200bps			
Power Saving Features	Sleep mode, Battery level indicator			
PTZ Address Scanning	Scan for local PTZ address over data cables			
Rechargeable Battery	6 hours charge, work for 10 hours			
Battery	1 pcs Lithium Ion Polymer Battery; 7.4V DC, 5000mAh			
Video Display	Displays video signal from analog input			
Video Signal	Color bar generator for monitor testing			
Cable Test	Checks connections of UTP cables, RJ45 cable TDR test			
PTZ Protocol	Compatible with more than 30 protocols such as PELCO-D/P, Samsung, Panasonic, TeleEye etc.			
PTZ data Capture	Reads and displays commands sent from controllers			
	4x zoom image display and video out			



Photograph	Snapshot and save the image as JPG file and screenshot				
Video record	Video recording and playback from the SD card				
Port Finder	Find the connected PoE port quickly				
IP scan	Find out the connected IP camera or network equipment's IP address				
Link monitor	Check the IP address whether is occupied				
Ping testing	Network and Ip camera ping testing				
PoE tester	PoE voltage testing, PoE port flicker, PoE link monitoring				
Night Led	Built Led lamp				
SD card	With 8G Micro SD card, support Micro SD card for recording, max support 32G SD card				
T . D	Screen projection: tester, mobile phone and PC display at the same time (For android version mobile				
Tester Play	phone)				
Drop-down menu	User can select PoE power switch, IP setting, WLAN switch, HDMI IN functions etc in any interface				
LID TVI innut	8MP TVI camera test, 3840 x 2160, 15 FPS, image display, zoom, video record and playback, coaxial PTZ				
HD-TVI input	control and call camera OSD menu				
HD-CVI input	8MP CVI camera test, 3840 x 2160, 12.5/15 FPS, image display, zoom, video record and playback, coaxial				
	PTZ control and call camera OSD menu				
AUD:	5MP AHD test, 2592 x 1944P, 12.5/20FPS, image display, zoom, video record and playback, coaxial PTZ				
AHD input	control and call camera OSD menu				
HD SDI/EX-SDI input	HD-SDI / EX-SDI camera test, support 1080P 50/60 FPS				
Multimeter	Voltage, current, resistance and capacitance can be tested, continuity testing, diode testing				
	Find out the connected cable from many messy cables. Connect one end of the cable to tester and the				
Cable Tracer	tester will send specific signals, which will enable the blue cable tracker to find out the other end of the				
	connected cable quickly and easily by making clearly sound.				
Video level meter	PEAK video signal level, SYNC signal level, COLOR BURST chroma level measurement				
Optical power meter	Testing the laser power of Video Fiber Optic Transmission equipment and Fiber Optic Patch Cord.				
Visual fault locator	Check fiber optical's breaking, cracking, bending failure etc (SM and MM fiber)				
TDR cable open circuit and short circuit measurement	Accurately measure BNC cable, network cable and telephone cable's break-point and short-circuits				
	location. TDR breakpoint will determine where the breakpoint is. And it can indicate the distance in				
	"meters" measuring in the tester. The farthest distance is 1200 meters.				
Dimension	240mm x 158mm x 44mm (Tester); 320mm x 290mm x 98mm (Colour box)				
Weight	1020 (Tester); 2770g (Tester with spare parts, black package, box)				

HD	720P	1080P	3МР	4MP	5MP	4K (8MP)
Resolution						
	1280 x 720 P	1920 x 1080 P	2048x1536 P	2688x1520 P 15FPS	2592 x 1944 P	3840 x 2160
TVI	25/30/50/60 FPS	25/30 FPS	18/25/30 FPS	2560x1440P 15/25/30 FPS	12.5/20FPS	15 FPS
CVI	1280 x 720 P	1920 x 1080 P		2560x1440 P		3840 x 2160
CVI	25/30/50/60 FPS	25/30 FPS		25/30 FPS		12.5/15 FPS
AHD	1280 x 720 P	1920 x 1080 P	2048x1536 P	2560x1440 P	2592 x 1944 P	
AHD	25/30 FPS	25/30 FPS	18/25/30 FPS	15/25/30 FPS	12.5/20FPS	



SDI Resolution	720P	1080P	1080i	
HD-SDI	1280 x 720 P	1920 x 1080 P	1920 x 1080 P	
	25/30/50/60 FPS	25/30/50/60 FPS	50/60 FPS	
EX-SDI	1280 x 720 P	1920 x 1080 P	1920 x 1080 P	
	25/30/50/60 FPS	25/30/50/60 FPS	50/60 FPS	