

IT-IPS-715-IM-1GC-4-POE

4-ports 10/100M Ethernet (POE) + 1-port Gigabit Combo

Managed Industrial POE Switch

Features

1. Support IEEE802.3, IEEE802.3u, IEEE 802.3x, IEEE802.3z/ab, IEEE802.1Q, IEEE802.1p, IEEE802.1D, IEEE802.1W.
2. Compatible with both IEEE802.3 at (30W) and IEEE802.3af (15.4W).
3. Supports 1 Gigabit combo ports and 4 Fast Ethernet copper ports.
4. SW-Ring ring network patent technology (Fault recovery time<20ms).
5. Support RSTP, way exchange time<50ms.
6. Support static multicast, IGMP Snooping and GMRP.
7. Support Port based VLAN and IEEE802.1Q VLAN.
8. Support QOS absolutely and opposite priority.
9. Support WEB, SNMP and Telnet configuration.
10. Support port status display, data update.
11. Industrial grade design, -40~75°C work temperature.
12. IP40 protection grade, DIN rail mounted.



1


Introduction

IT-IPS-715-IM-1GC-4-POE is an industrial grade, managed and redundancy Ethernet switch. The switch provides 4 ports 10/100M Ethernet and 1 ports combo Gigabit SFP slots or 10/100/1000Base-T(X) ports, which 4 ports Ethernet supports POE function (IEEE802.3af/at). It provided some kinds of advanced network managed function, like as: SW-Ring redundancy ring

network, VLAN, Trunking, Quality of Service, Speed control, port mirroring and fault alarm. SW-Ring can bring your Ethernet to intelligent redundancy. The -40~75°C working temperature can meet all kinds of Industrial environment requirement and provide the solution of the economy.

Dimensions

Unit (mm)



Specifications

Technology

Standard: Support IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3z/ab, IEEE802.1Q, IEEE802.1p, IEEE802.1D, IEEE802.1W
Flow control: IEEE802.3x flow control, back press flow control
POE Standard: IEEE802.3af/at

Exchange attributes

100M forward speed: 148810pps
1000M forward speed: 1488100pps
100M maximum filter speed: 148810pps
1000M maximum filter speed: 1488100pps
Transmit mode: store and forward
System exchange bandwidth: 7.6G
MAC address table: 8K
Memory: 1M

Interfaces

Fast Ethernet Port: 10Base-T/100Base-TX auto speed control, Half/full duplex and MDI/MDI-X auto detect
PoE Pin-out: 1/2(+), 3/6(-)
Gigabit Combo port: 1000Base-X SFP slot or 10/100/1000Base-T(X)
Console port: debug serial port carry out CLI command
Alarm port: Two bit 7.62mm terminal block
One channel relay alarm output

Transfer distance

Twisted cable: 100M (standard CAT5/CAT5e cable)
Multi-mode: 1310nm, 2Km
Single-mode: 1310nm, 20/40/60Km
1550nm, 80/100/120Km

LED indicators

Run indicator: Run
Interface indicator: Link (1~4/G1)
POE indicator: 1~4
Power supply indicator: P1, P2
Alarm indicator: Alarm

Power supply

Input Voltage: 44~57VDC
Type of input: 4 bits 7.62mm terminal block
No-load consumption: 7W@48VDC
Full-load consumption: 60W@48VDC
Single PoE port maximum consumption: 30W@48VDC

Working environment

Working temperature: -40~75°C
Storage temperature: -40~85°C
Relative Humidity: 5%~95% (no condensation)

Mechanical Structure

Shell: IP40 protect grade, metal shell
Installation: DIN rail mount
Size (W×H×D): 70mm×160mm×130mm
Weight: 1.0kg

Industry Standards

EMI: FCC Part 15, CISPR (EN55022) class A
EMS: EN61000-4-2 (ESD)
EN61000-4-4 (EFT)
EN61000-4-5 (Surge)
Shock: IEC 60068-2-27
Free fall: IEC 60068-2-32
Vibration: IEC 60068-2-6

Warranty: 5 years

Packing List

1. Industrial PoE Switch (plus terminal block) ×1
2. User manual ×1
3. Documentation and software CD ×1
4. Certificate of quality ×1
5. Warranty card ×1
6. DIN-Rail mounting kit ×1