

IT-ES3020-4GS-2F (12-48VDC)

14 ports 10Base-T/100BaseTX + 2 ports 100Base-FX + 4 ports 1000Base-FX SFP

Features

1. Support 14 ports 10Base-T/100Base+ 2 port 100Base-FX+ 4 port 1000Base-FX SFP
2. Support MAC address auto-learning, auto-aging.
3. Support 8K MAC address table
4. System exchange bandwidth: 11.2Gbps
5. Support redundancy power supply (12 ~ 48VDC), non-polarity
6. Support flow control
7. Support Broadcast storm suppression
8. Support 1ch relay alarm output
9. Working temperature: -40°C~ 85°C
10. DIN rail mounted
11. No fan, low consumption.
12. Metal shell, IP40 protection class.




1

Introduction

IT-ES3020-4GS-2F (12-48VDC) is an unmanaged Industrial Ethernet switch with high performance, high cost-effective. It provided 14 ports 10Base-T/100Base-TX Ethernet+ 2 ports 100Base-FX optic fiber + 4 ports 1000Base-FX SFP slot. It supports

auto flow control, full/half duplex mode and MDI/MDI-X self-adaption. It built in standard industry design, all components are based on Industry grade, no fan, low consumption, can satisfied some kinds of requirements of industry field, to achieve high reliability.

Dimensions and appearance



Specifications

Technology

Standard: IEEE802.3, IEEE802.3u, IEEE802.3x

Flow control: IEEE802.3x, back pressure

Interfaces

Electric port: 10Base-T/100Base-TX auto speed control, Half/full duplex and MDI/MDI-X auto detection

100M fiber port: 100Base-FX, SC/ST optional

1000M fiber port: 1000Base-FX (SFP port)

Alarm port: 2bit 7.62mm Terminal block

1 channel relay alarm output

Transfer distance:

Twisted cable: 100M (standard CAT5/CAT5e cable)

Multi mode fiber: 1310nm, 2Km

Single mode fiber: 1310nm, 20/40/60Km

1550nm, 60/80/100/120Km

Exchange attributes:

100M forward speed: 148810pps

1000M forward speed: 1488100pps

100M maximum filter speed: 148810pps

1000M maximum filter speed: 1488100pps

Transmit mode: store and forward

System exchange bandwidth: 11.2G

MAC address table: 8K

Memory: 256Kbits

LED indicators

Power supply indicator: P1, P2

Alarm indicator: ALARM

Running status indicator: RUN

100M port connection/running status: Link/Act (1~16)

1000M port connection/running status: Link/Act (G1~G4)

Power supply

Input voltage: 12~48VDC

Input method: 4 bits 7.62mm terminal block

No-load consumption: 5.86W@24VDC

Full-load consumption: 10.63W@24VDC

Support DC dual power supply redundancy

Overload current protect: 4.0A (DC)

Power supply support non-polarity

Mechanical Structure:

Shell: IP40 protect grade, metal shell

Installation: DIN rail and wall mount

Size (W×H×D): 160mm×130mm×70mm

Weight: 1016g

Working environment:

Working temperature: -40~85°C

Storage temperature: -40~85°C

Relative Humidity: 5%~95% (no condensation)

Standards

EMI: FCC Part 15, CISPR (EN55022) class A

EMS: EN61000-4-2 (ESD), Level 4

Shock: IEC 60068-2-27

Free fall: IEC 60068-2-32

Shake: IEC 60068-2-6

Warranty

Warranty time: 5 years

Certifications

CE, FCC, RoHS, UL508 (Pending)

Ordering informations

| Model name | Port | | | | | | Power |
|--------------------------------|-----------|----|-----------------|----|----|----|---------------|
| Model name (-40°C ~ 85°C) | 1000M(LC) | | 100M fiber port | | | | 100M Ethernet |
| | SM | MM | SM | | MM | | |
| | | | SC | ST | SC | ST | |
| IT-ES3020-4GS-2F (12-48VDC) | 4 | - | 2 | - | - | - | 14 |
| | 4 | - | - | 2 | - | - | 14 |
| | 4 | - | - | - | - | - | 14 |
| | 4 | - | - | - | 2 | - | 14 |
| | 4 | - | - | - | - | 2 | 14 |
| | 4 | - | - | - | - | - | 14 |
| | | 4 | 2 | - | - | - | 14 |
| | | 4 | - | 2 | - | - | 14 |
| | | 4 | - | - | - | - | 14 |
| | | 4 | - | - | 2 | - | 14 |
| | | 4 | - | - | - | 2 | 14 |
| | | 4 | - | - | - | - | 14 |