

# IT-DAN-209

## Indoor Directional Pickup

### FEATURES

- Pickup Distance: Effective Distance: 0-2 Meters
- Microphone: Professional High SNR: MEMS
- Signal Processing Circuit: Professional Hi-fidelity Low Noise Audio Processor
- Working Temperature: -40°C ~ +85°C
- Waterproof Characteristic: Indoor Damp proof
- Applicable To Bank Closed Counter, Service Windows, Seat etc.



### SPECIFICATIONS

Model No.	<b>IT-DAN-209</b>
Type	Indoor Directional Pickup
Pickup Distance	0-2m
Transmission Distance	3000m
SNR	65dB at1KHz at 1Pa
Dynamic Range	98dB (1KHz at Max dB SPL)
Sensitivity	-38dB
Max. Sustainable Sound Pressure	127dB SPL (1KHz, THD 1%)
Directional Characteristic	Single Directional
Frequency Response	20Hz ~ 20kHz
Output Impedance	600Ω (non-equilibrium)
Signal Processing Circuit	Professional Audio Processor
Waterproof	Indoor Damp proof
Output Signal Amplitude	2.5Vpp/-25db
Microphone	Directional
Sound Head Qty	Single Sound Head
Protection Circuit	Lightning Protection, Power Polarity Reversal Protection
Transmission Cable	3 Cores 0.5mm 2 RVVP Shielded Cable
Working Voltage	DC 12V
Working Current	20 Ma
Working Temperature	-40°C ~ +85°C
Color	White
Material	PVC
Dimension	43mm×24mm×8mm
Weight	30g

### DIMENSIONS (mm)

