

# IT-9002-H-NVR

# IT-2520-H-NVR

**Embedded HD Network Video Recorder**



## FEATURES

- The Preview Screen can be changed at will, The Image Position changed, The Physical Address will not be changed;
- Support 15X Digital Enlarge, Dragging any Enlarged Image by Mouse (Preview/Playback);
- Support Instant Capture, and set a Separate-Area to save the Screenshot in the HDD;
- Recording Playback is shown by Time Bar, Different Colors displays Different Recording Type, Fast and easy for checking the Recording;
- Support USB Disk Backup File Playback on Host Directly (Backup can be accurate to the seconds);
- HDD Sequence Writing Method, start writing Data from zero tracks, Enhance the Efficiency of HDD Read and Write.

## SPECIFICATIONS

Model No.	<b>IT-9002-H-NVR</b>		<b>IT-2520-H-NVR</b>
Operating System	Embedded Linux O.S		
Image Coding Control	Image Coding Quality can be adjusted, VBR /CBR Optional		
Dual Stream	Each Channel can be set;		
Video Standard	H.264		
Image Quality	5MP(2592×1944)/ 3MP(2048×1536)/ 1080P(1920×1080)/ 960P(1280×960)/ 720P(1280×720)		
Image Dynamic Detection	Each Screen can detect Multiple Detection Regions, 6 levels Sensitivity can be set;		
Playback	1/4/9CH Sync. Playback	1/4/8CH Sync. Playback;	
Privacy Mask	Each Channel support 4 Privacy Mask Areas (need IPC support);		
Recording Mode	Support Manual, Auto, Dynamic Detection, Alarm Trigger Recording Mode (Partly need IPC support);		
Backup Mode	Support HDD , U Disk, USB Mobile HDD , USB Record, Network Storage and Backups (Partly need IPC support);		
Operating Mode	Mouse;		
Local Login	User Name /Password;		
Recording Storage	Local HDD , Remote Network Host;		
External Interface	Network Video Input (Mode)	9×(1280*960)+Sub[960*576]+4Ref.+9Play	25×(1280*960)+Sub[720*576]+4Ref.+8Play
		9×(2048*1536)+Sub[960*576]+4Ref.+4Play	16×(2048*1536)+Sub[960*576]+4Ref.+4Play
		9×(2592*1944)+Sub[960*576]+4Ref.+1Play	9×(2592*1944)+Sub[960*576]+4Ref.+1Play
		9×(2592*1944)+Sub[1280*960]+4Ref.+1Play	//////////////////////////////////// ////////
	Audio Input	1:1 Network Audio Input by Network Video Channel No;	
	Video Output	1CH VGA + 1CH HDMI;	
	Audio Output	1CH RCA;	
	Network Interface	1*RJ45;	
	RS485 Interface	Full Duplex Standard RS485 Interface;	
	USB Interface	2*USB2.0 Interface;	
Alarm Input	2CH (Optional);		
Alarm Output	1CH (Optional);		

HDD	HDD Interface	2*HDD Interface;
	Max. Capacity	Each SATA Interface support Max. 6TB HDD;
Mobile Surveillance		Support
Power Supply		DC12V/3A
Consumption		≤20W (without HDD);
Working Temperature		-10°C ~ 55°C
Working Humidity		10%-90%
Dimensions		NVR: 350mm×240mm×70mm, with Package: 409mm×365mm×129mm;
Weight (without HDD)		Net Weight: 1.7kg, with Package: 2.9kg;
Carton		5 units/Carton, Dimension: 675mm×425mm×385mm, Weight: 15.3kg;
Installation		Desktop Installation.

## DIMENSIONS (Unit: mm)

