

IT-3691KGH-NVR

IT-6491KGH-NVR

Embedded HD Network Video Recorder



FEATURES

- The Preview Screen can be changed at will, The Image Position changed, The Physical Address will not be changed;
- Support 15X Digital Enlarge, Dragging any Enlarged Image by Mouse (Preview/Playback);
- Support Instant Capture, and set a Separate-Area to save the Screenshot in the HDD;
- Recording Playback is shown by Time Bar, Different Colors displays Different Recording Type, Fast and easy for checking the Recording;
- Support USB Disk Backup File Playback on Host Directly (Backup can be accurate to the seconds);
- HDD Sequence Writing Method, start writing Data from zero tracks, Enhance the Efficiency of HDD Read and Write.

SPECIFICATIONS

Model No.	IT-3691KGH-NVR		IT-6491KGH-NVR	
Operating System	Embedded Linux Operating System			
Image Coding Control	Image Coding Quality can be adjusted, VBR/ CBR Optional			
Dual Stream	Each Channel can be set			
Video Standard	H.265/ H.264			
Image Quality	4K(3840×2160) / 5MP(2592×1944) / 3MP(2048×1536) / 1080P(1920×1080) / 960P(1280×960) / 720P(1280×720)			
Image Dynamic Detection	Each Screen can detect Multiple Detection Regions, 6 levels Sensitivity can be set			
Image Playback	1 1/4/9/16CH Sync. Playback		1/4/9/16CH Sync. Playback	
Privacy Mask	Each Channel support 4 Privacy Mask Areas (need IPC support);			
Recording Mode	Support Manual, Auto, Dynamic Detection, Alarm Trigger Recording Mode			
Backup Mode	Support Hard Disk, U Disk, USB Mobile Hard Disk, USB Record, Network Storage and Backups (Partly need IPC support);			
Operating Mode	Mouse, Keyboard			
Local Login	User Name / Password			
Recording Storage	Local Hard Disk, Remote Network Host			
External Interfaces	Network Video Input	36×[3840*2160]+sub[960*576] +4Ref.+4Play		64×[3840*2160]+sub[960*576] +4Ref.+4Play
		36×[2048*1944]+sub[960*576] +4Ref.+9Play		64×[2048*1944]+sub[960*576] +4Ref.+9Play
		36×[1920*1080]+sub[960*576] +4Ref.+16Play		64×[1920*1080]+sub[960*576] +4Ref.+16Play
	Audio Input	1:1 Network Audio Input by Network Video Channel Number;		
	Video Output	1CH VGA + 1CH HDMI		
	Audio Output	1*RCA		
Network Interface	1*RJ45		*RJ45	

	S485 Interface	Full Duplex Standard RS485 Interface
	USB Interface	1*USB3.0 Interface, 2*USB2.0 Interface
	Alarm Input	4ch
	Alarm Output	4ch
Hard Disk	Hard Disk Interface	9*SATA+1*E-SATA
	Max. Capacity	Each SATA Interface support Max. 6TB Hard Disk;
Mobile Surveillance		Support
Power Supply		ATX110-220V 200W 50-60Hz
Consumption		≤30W (without HDD)
Working Temperature		-10°C ~ 55°C
Working Humidity		10%-90%
Dimensions		440mm×432mm×90mm, With Package: 539mm×550mm×225mm
Weight (without HDD)		Net Weight: 7.4Kg; with Package: 9.8Kg
Carton		2pcs 1 carton. Dimensions: 555mm×545mm×470mm; Weight: 21 Kg.
Installation		Desktop Installation, Standard Rack Installation

DIMENSIONS (Unit : mm)

