

# IT-4002KGH-NVR IT-8002KGH-NVR IT-1620KGH-NVR

Linux Network Video Recorder



## FEATURES

- Support ONVIF, 4K HD Network Video Preview, Storage / Playback;
- Support H.265, H.264, IPC Centralize Management includes IPC Parameter Configuration, Information I/O, Audio Intercom and Upgrade, etc.
- HDMI Output Up To 3840×2160; Brand-new UI Interface, One key to open recording;
- Support Instant Playback, Specified Channel Video Playback under the Preview Screen without affecting other channels;
- Support Event, Query, Playback Recording File; Double Users Certification;
- Support HDD Quota and Group Storage Mode, Allocate Different Saving Spaces / Cycle of Recording for Different Channels.

## SPECIFICATIONS

Model No.		IT-4002KGH-NVR	IT-8002KGH-NVR	IT-1620KGH-NVR
Operation System		LINUX O.S		
Video & Audio Input	Network Video Input	4CH Network Compress Video Input	8CH Network Compress Video Input	16CH Network Compress Video Input
	Audio Input	IPC Composite Audio Input		
Video & Audio Output	HDMI Output	1CH, Resolution: 4K(3840*2160)/30Hz, (1920*1080)/60Hz		
	Audio Output	1*RCA Port		
Video & Audio Encode	Video Standard	H.265 /H.264 /MJPEG		
	Recording Resolution	8M/5M/3M/1080P/720P		
	Decode Playback	Up To 4CH 1080P Playback		
Recording	Record/Snapshot	Manual Recording, Timer Recording, Event Recording, Motion Detection Recording, Alarm Recording		
	Playback	Instant Playback, Routine Playback, Event Playback, External File Time-Phased Playback, Routine Playback, Event Playback, External File Playback, Log Playback		
	Backup	Routine Backup, Event Backup, Record Cutting Backup		
HDD	HDD Port	2*SATA Ports		
	Max Capacity	Each Port supports Max. 6TB HDD		
External	Network Port	1 Port, RJ45 1*RJ45		
	USB Port	3 Ports(1*USB2.0 Port in Front, 2*USB2.0 Ports at Back-end)		
	Serial Port	1* RS-485 1*RS-485		
	Alarm Input	4CH Alarm Input, Low Electrical Level Effective, Green Connection Line Port		
	Alarm Output	1CH Alarm Output, Relay Touch (1A@24VDC), NO, NC can Program		
Network	Network Protocol	ONVIF (2.4), IPv4, UPnP (Plug & Play), NTP (Network Timing), SADP (Auto Search IP Address), PPPoE (Dial-up), DHCP (Auto get IP Address), etc.		
Others	Mobile Surveillance	Support		
	Power Supply	DC 12V3A		
	Power Consumption (Without HDD)	< 10W (Without HDD)		
	Working Temperature	-10°C ~ 55°C		
	Working Humidity	10%~90%		
	Dimensions	NVR: 1.5U, 350mm(W)*240mm(L)*68mm(H); Packing: 414mm*370mm*134mm		
	Weight (Without HDD)	N.W: 1.7KG; With Packing: 2.9KG		
	Carton	5pcs/Carton; Dimension: 675mm*425mm*385mm; Weight: 15.3 KG		
Installation	Desktop Installation			

**DIMENSIONS** (Unit : mm)

