

IT-9946MIG50-HD-3MP IT-9946AIG50-HD-3MP

Onvie

3.0 Megapixel HD Network Starlight IR 50M Bullet Camera

FEATURES

- Starlight Low Illumination
- H.265/H.264/M-JPEG, Support Multiple Code Stream
- HDTV 3MP Full Real-Time Transmission
- Support ONVIF, Built-in Auto Double Filter Switching Mechanism, True Day/Night
- Support 3D DNR, Mobile Surveillance, IR 50M, Weatherproof IP66
- Support WDR, DC12V/AC24V/POE

















SPECIFICATIONS

Model	Model No.		IT-9946MIG50-HD-3MP	IT-9946AIG50-HD-3MP
	Туре		3 Megapixel HD Network Starlight IR 50M Bullet Camera	
Camera	Sensor		1/2.8"Progress Scan CMOS	
	Resolution	Main Stream	2048*1536, 1-25(30)FPS; 1920*1080, 1-25(30)FPS; 1280*720, 1-25(30)FPS	
	Resolution	Sub Stream	704*576, 1-25(30)FPS; 640*480, 1-25(30)FPS	
	Min. Illumination		Color 0.001Lux@F1.2; B/W 0LUX (IR ON)	
	IR Distance		50M, 4pcs Array LED	
	S/N Ratio		≥52db	
	WDR		≥120db	
	Electronic Shutter		1~ 1/10000 sec, Automatic	
	Lens		2.8-12mm Manual Zoom Lens	2.8-12mm HD Motorized Focus Lens
	Day & Night		IR Cut Optical Filter	
Audio/ Video Setting	Video Compression		H.265/H.264/M-JPEG, Support Multiple Code Stream	
	Code Stream		32Kbps-16Mbps, Support CBR/VBR	
	Video Adjustment		Brightness / Contrast / Chroma / Saturation / Sharpness / GAMMA	
	Intelligent Features		Intelligent Code Stream, Video Mask, Out-of-focus Detection, Intelligent Switch Control	
	Image Flip		Horizontal, Vertical, Horizontal & Vertical	
	Motion Detection		Support	
	Privacy Mask		Support	
	3D DNR		High/Medium/Low	
	OSD Setting		Support Channel Name, Date Time, Code Stream Overlay	
Network	Interface		10/100 M Ethernet (RJ-45)	
	Protocol		TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, SMTP,	
	ONVIF		Onvif 2.4	
	Access Control		Administer and Common User	
	Web Browser		IE 6.0 and Above	
	Max. User Number		≤10	
Interfaces	CVBS/BNC		Support	
	Audio I/O		Support	
	Alarm I/O		Support	
	RS485		Support	
	Mobile Surveillance		Support	
	IP Grade		IP 66	
General	Working Conditions		-20°C ~ 60°C; 10% to 90% (Non-Condensing)	
	Power Supply		DC12V/AC24V/POE	
	Dimensions (mm)		345(L) x100(W)x100(H)mm	
	Weight (with package)		990g	

For Financial, Prison, Supermarket, Telecom, Government, School, Airport, Factory, Hotel, and Other Indoor / Outdoor Places.









