

IT-1636MIG-A-HD-4MP IT-1636AIG-A-HD-4MP

4.0 Megapixel HD Network IR Indoor Plastic Dome Camera

Intellisystem

ONVIE

FEATURES

- H.265/H.264/M-JPEG, Support Multiple Code Stream
- HDTV, Support 4MP Full Real-Time Transmission
- Support ONVIF, Built-in Auto Double Filter Switching Mechanism, True Day/Night
- Support 3D DNR, Mobile Surveillance, IR 30M
- Support WDR, DC12V/AC24V/POE













SPECIFICATIONS

Madal	Model No		IT-1636MIG-A-HD-4MP	IT-1636AIG-A-HD-4MP
Model	Туре		4.0 Megapixel HD Network IR Indoor Plastic Dome Camera	
Camera	Sensor		1/3" Progress Scan CMOS	
	5 1	Main Stream	2592*1520, 1-25(30)FPS; 2040*1536	i, 1-25(30)FPS; 1920*1080, 1-25(30)FPS
	Resolution	Sub Stream	704*576, 1-25(30)FPS; 640*480, 1-25(30)FPS
	Min. Illumination		Color 0.1Lux @F1.2; B/W 0Lux @F1.2 (IR ON)	
	IR Distance		IR 30M, 24pcs IR LED	
	S/N Ratio		≥52db	
	WDR		≥120db	
	Electronic Shutter		1~ 1/10000 sec, Auto	
	Lens		2.8-12mm Manual Zoom Lens	2.8-12mm HD Motorized Focus Lens
	Day & Night		IR Cut Optical Filter	
Audio/Video Setting	Video Compression		H.265/H.264/M-JPEG, Support for Multiple Output Code	
	Code Stream		32Kbps-16Mbps, Support CBR/VBR	
	Video Adjustment		Brightness/ Contrast / Chroma/ Saturation/ Sharpness / GAMMA	
	Intelligent Features		Intelligent Code Stream, Video Mask, Out-of-focus Detection, Intelligent Switch	
			Control	
	Image Flip		Horizontal, Vertical, Horizontal & Vertical	
	Motion Detection		Support	
	Privacy Mask		Support	
	3D DNR		High/Medium/Low	
	OSD Setting		Support Channel Name, Date Time, Code Stream Overlay	
Network	Interface		10/100 M Ethernet (RJ-45)	
	Protocol		TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, SMTP, UPNP	
	ONVIF		Onvif 2.4	
	Access Control		Administer and Common User	
	Web Browser		IE 6, 0 and Above	
	Max. User Number		≤10	
Interfaces	CVBS/BNC		Support	
	Audio I/O		Support	
	Alarm I/O		Support	
	RS485		Support	
	TF Card		Support	
	Mobile Surveillance		Support	
General	Working Conditions		-20°C ~ 60°C; 10% to 90% (Non-Condensing)	
	Power Supply		POE/AC24V/DC12V ±10%	
	Dimensions (mm)		150(Φ)x100(H)mm	
	Weight (with package)		355g	

For Financial, Prison, Supermarket, Telecom, Government, School, Airport, Factory, Hotel and Other Indoor Places.



DIMENSIONS (Unit:mm)



