

IT-9637MG-HD-5MP IT-9637AG-HD-5MP

Onvie

5.0 Megapixel HD Network Ultra Starlight Indoor Dome Camera

FEATURES

- •Starlight Low Illumination, H.265/H.264/M-JPEG, Support Multiple Code Stream
- HDTV, Support 5 MEG Full Real-Time Transmission
- Support ONVIF, Built-in Auto Double Filter Switching Mechanism, True Day/Night
- Support 3D DNR, Mobile Surveillance
- Support WDR, DC12V/AC24V/ POE















SPECIFICATIONS

| Model | Model No. | | IT-9637MG-HD-5MP | IT-9637AG-HD-5MP | |
|----------------------------|-----------------------|-------------|--|----------------------------------|--|
| Model | Туре | | 5 Megapixel HD Network Ultra Starlight Indoor Dome Camera | | |
| Camera | Sensor | | 1/1.8" Scan CMOS | | |
| | Resolution | Main Stream | 2592*1944, 1-25(30) FPS; 2560*1920, 1-25(30) FPS; 2048*1536 , 1-25(30) FPS; | | |
| | | Sub Stream | 704*576, 1-25(30)FPS; 640*480, 1-25(30)FPS | | |
| | Min. Illumination | | Color 0.005Lux@F1.2; B/W 0.0005Lux@F1.2 | | |
| | S/N Ratio | | ≥52db | | |
| | WDR | | ≥120db | | |
| | Electronic Shutter | | 1~ 1/10000 sec. Auto | | |
| | Lens | | 3.6-10mm 6MP Manual Zoom Lens | 3.6-10mm6MP Motorized Focus Lens | |
| | Day & Night | | IR Cut Optical Filter | | |
| Audio/ Video Setting | Video Compression | | H.265/H.264/M-JPEG, Support Multiple Code Stream | | |
| | Code Stream | | 32Kbps-16Mbps, Support CBR/VBR | | |
| | Video Adjustment | | Brightness/ Contrast / Chroma/ Saturation/ Sharpness / GAMMA | | |
| | Intelligent Features | | Intelligent Code Stream, Video Mask, Out-of-focus Detection, Intelligent Switch | | |
| | Image Flip | | Horizontal, Vertical, Horizontal & Vertical | | |
| | Motion Detection | | Support | | |
| | Privacy Mask | | Support | | |
| | 3D DNR | | High/Medium/Low | | |
| | OSD Setting | | Support Channel Name, Date Time, Code Stream Overlay | | |
| Network | Interface | | 10/100 M Ethernet (RJ-45) | | |
| | Protocol | | TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, SMTP, UPNP | | |
| | ONVIF | | Onvif 2.4 | | |
| | Access Control | | Administer and Common User | | |
| | Web Browser | | IE 6.0 and Above | | |
| | Max. User Number | | ≤10 | | |
| Interfaces | CVBS/BNC | | Support | | |
| | Audio I/O | | Support | | |
| | Alarm I/O | | Support | | |
| | RS485 | | Support | | |
| | TF Card | | Support | | |
| | Mobile Surveillance | | Support | | |
| General | Working Conditions | | -20°C ~ 60°C; 10% to 90%, (Non-Condensing) | | |
| | Power Supply | | POE/DC12V/AC24V ±10% | | |
| | Dimensions (mm) | | 150(Φ)x100(H)mm | | |
| | Weight (with package) | | 355g | | |

For Financial, Prison, Supermarket, Telecom, Government, School, Airport, Factory, Hotel and other Indoor Places.



DIMENSIONS (Unit:mm)



