

IT-9637MIG-HD-5MP IT-9637AIG-HD-5MP

Onvie

5.0 Megapixel HD Network Ultra Starlight IR Indoor Dome Camera

brellisystes

FEATURES

- Starlight Low Illumination, H.265/ H.264/ M-JPEG, Support Multiple Code Stream
- HDTV, Support 5 MEG Full Real-Time Transmission
- Support ONVIF, Built-in Auto Double Filter Switching Mechanism, True Day/Night
- Support 3D DNR, Mobile Surveillance, IR 30M&24pcs IR LED
- Support DC12V/AC24V/POE















SPECIFICATIONS

Model	Model No.		IT-9637MIG-HD-5MP	IT-9637AIG-HD-5MP
Model	Туре		5 Megapixel HD Network Ultra Starlight IR Indoor Dome Camera	
Camera	Sensor		1/1.8" Scan CMOS	
	Resolution	Main Stream	2592*1944, 1-25(30) FPS; 2560*1920, 1-2	25(30) FPS; 2048*1536, 1-25(30)
		Sub Stream	704*576, 1-25(30)FPS; 640*480, 1-25(30))FPS
	Min. Illumination		Color 0.005Lux@F1.2; B/W 0Lux@F1.2 (IR ON)	
	IR Distance		IR 30M, 24pcs IR LED	
	S/N Ratio		≥52db	
	WDR		≥120db	
	Electronic Shutter		1~ 1/10000 sec. Auto	
	Lens		3.6-10mm 6MP Manual Zoom Lens	3.6-10mm 6MP Motorized Focus
	Day & Night		IR Cut Optical Filter	
Audio/ Video Setting	Video Compression		H.265/ H.264/M-JPEG, Support Multiple Code Stream	
	Code Stream		32Kbps-16Mbps, Support CBR/VBR	
	Video Adjustment		Brightness/ Contrast / Chroma/ Saturation/ Sharpness / GAMMA	
	Intelligent Features		Intelligent Code Stream, Video Mask, Out-of-focus Detection, Intelligent Switch	
	Image Flip		Horizontal, Vertical, Horizontal & Vertical	
	Motion Detection		Support	
	Privacy Mask		Support	
	3D DNR		High/Medium/Low	
	OSD Setting		Support Channel Name, Date Time, Code Stream Overlay	
Network	Interface		10/100 M Ethernet (RJ-45)	
	Protocol		TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, SMTP,	
	ONVIF		Onvif 2.4	
	Access Control		Administer and Common User	
	Web Browser		IE 6.0 and Above	
	Max. User Number		≤10	
Interfaces	CVBS/BNC		Support	
	Audio I/O		Support	
	Alarm I/O		Support	
	RS485		Support	
	TF Card		Support	
	Mobile Surveillance		Support	
General	Working Conditions		-20°C ~ 60°C; 10% to 90%, (Non-Condensing)	
	Power Supply		POE/DC12V/AC24V±10%	
	Dimensions (mm)		150(Φ)x100(H)mm	
	Weight (with package)		355g	

For Financial, Prison, Supermarket, Telecom, Government, School, Airport, Factory, Hotel and Other Indoor Places.



DIMENSIONS

(Unit:mm)



