

IT-314PRI-HD-1MP IT-324PRI-HD-2MP

HD Network IR Bullet Camera



FEATURES

- HDTV Image Quality, Support 720P/1024P/1080P/ 3 Megapixel Real-Time
- Support ONVIF
- Support 3D DNR, DC12V, Weatherproof IP66, Mobile Surveillance

SPECIFICATIONS

| Model | Model No. | | IT-314PRI-HD-1MP | IT-324PRI-HD-2MP |
|-----------------------------|---------------------|-------------------|--|---|
| | | Type | | 1.3 Megapixel HD IR Bullet Camera |
| Camera | Image Sensor | | 1/3" Progress Scan CMOS | 1/2.8" Progress Scan CMOS |
| | Resolution | Main Stream | 1280*1024,1-25(30)Fps | 1920*1080,1-25(30)Fps |
| | | Sub Stream | 720*576,1-25(30)Fps;640*480,1-25(30)Fps | |
| | Min. Illumination | | Color 0.01Lux@F1.2; B/W 0Lux@F1.2 (IR ON) | Color 0.01Lux@F1.2; B/W 0Lux@F1.2 (IR ON) |
| | S/N Ratio | | ≥50db(AGC OFF) | |
| | WDR | | ≥80db | |
| | Electronic Shutter | | 1~ 1/10000 sec. Auto | |
| | Lens | | 3.6/6mm (Optional) | |
| | Day/Night | | EI (ICR Optional) | |
| | IR Distance | | 30m, 36pcs Led | |
| Audio/ Video Settings | Compression | | H.264 (Baseline, Main Profile)/M-PEG | H.265/ H.264 (Baseline, Main Profile)/ M- |
| | Code Stream | | 32Kbps-16Mbps Adjustable, Support CBR/VBR The Code Rate& Frame Rate of LAN & WAN can be respectively set upon the same code stream | |
| | Video Adjustment | | Brightness/Contrast/Chromatic /Saturation/ Sharpness /GAMMA | |
| | Electronic Shutter | | 1/25~1/8000 | |
| | Image Flip | | Support | |
| | Motion Detection | | Support | |
| | Privacy Mask | | Support | |
| | 3D DNR | | High/ Middle/ Low | |
| Network | OSD | | Support Channel Name , Date and Stream Overlay, the position adjustable | |
| | Interface | | 10/100 M Ethernet (RJ-45) | |
| | Protocol | | TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, SMTP, UPNP | |
| | ONVIF | | Support | |
| | Access Control | | Administer and Common User | |
| | Web Browser | | IE 6.0 and above | |
| General | Max. User Number | | ≤10 | |
| | Audio I/O | | Optional | |
| | Adjustment Range | | 3-Axis Rotation | |
| | Mobile Surveillance | | Support | |
| | Working Condition | | -10°C ~ 50°C; 10% to 90%, Non-condensing | |
| | Power Supply | | DC12V | |
| | IP Rating | | IP66 | |
| Dimensions (mm) | | 204.65 x 65.83 mm | | |
| Weight (with package) | | 400g | | |

DIMENSIONS (Unit : mm)