

# IT-513PRI-HD-1MP IT-523PRI-HD-2MP

## HD IR IP Vandal Proof Mini Dome Camera



### FEATURES

- HDTV Image Quality, Support 1024P/1080P Real-Time
- Support Onvif
- Support 3D DNR, DC12V
- Mobile Surveillance (Optional) Vandal Proof

### SPECIFICATIONS

Model	Model No.		IT-513PRI-HD-1MP	IT-523PRI-HD-2MP
	Type		1.3 Megapixel HD IR Dome camera	2 Megapixel HD IR Dome camera
Camera	Image Sensor		1/3"Progress Scan CMOS	
	Resolution	Main Stream	1280*960, 1-25(30)Fps 1280*720, 1-25(30)Fps	1920*1080, 1-25(30)Fps 1280*720, 1-25(30)Fps
		Sub Stream	640*480, 1-25(30)Fps; 480*360, 1-25(30)Fps; 176*144, 1-25(30)Fps	
	Min. Illumination		Color: 0.1Lux@F1.2; B/W:0Lux@F1.2 (IR ON)	Color: 0.01Lux@F1.2; B/W:0Lux@F1.2 (IR ON)
	S/N Ratio		≥50db(AGC OFF)	
	WDR		80db	
	Electronic Shutter		1~ 1/10000 sec., Auto	
	Lens		2.8/3.6/6mm	
	Day/Night		EI (ICR Optional)	
	IR Distance		10M/12Pcs LED	
Audio/Video Settings	Compression		H.264 (Baseline, Main Profile)/M-JPEG	H.265/H.264 (Baseline, Main Profile)/M-JPEG
	Code Stream		32Kbps-16Mbps Adjustable, Support CBR/VBR The Code Rate & Frame Rate of LAN & WAN can be respectively set upon the same code stream	
	Video Adjustment		Brightness/Contrast/Chromatic /Saturation/ Sharpness /GAMMA	
	Electronic Shutter		1/25~1/8000	
	Image Flip		Support	
	Motion Detection		Support	
	Privacy Mask		Support	
	3D DNR		High/ Middle/ Low	
OSD		Support Channel Name , Date and Stream Overlay, the position adjustable		
Network	Interface		10/100 M Ethernet (RJ-45)	
	Protocol		TCP/IP、UDP、RTP、RTSP、RTCP、HTTP、DNS、DDNS、DHCP、FTP、NTP、PPPOE、SMTP、UPNP	
	ONVIF		Support	
	Access Control		Administer and Common User	
	Web Browser		IE 6.0 and above	
	Max. User Number		≤10	
General	Audio Input / Output		Optional	
	Adjustment Range		3-Axis Rotation	
	Mobile Surveillance		Support	
	Working Condition		-10°C ~ 50°C; 10% to 90%, Non-condensing	
	Power Supply		DC12V	
	Vandal-proof		IK10	
	IP Rating		IP66	
	Dimensions (mm)		110(Φ)x60(H)mm	
Weight (with package)		350g		

**DIMENSIONS** (Unit : mm)

