

IT-3295LG-TPS-PTZ-HD-2MP

2.0 MP HD Mobile PTZ Camera

FEATURES

- White Light For Night Vision: Adopt High-end Array Lens
Long Life Time Around 30000 Hours, White Light Distance: 100-150m
- Network HD: Support Megapixel HD Sensor and High-definition Image Acquisition
ONVIF Compatible, Support 1080P Output, Dual- Stream & High-Definition Capture, IE Browse, etc.



SPEIFICATIONS

Model	Model No.	IT-3295LG-TPS-PTZ-HD-2MP
	Type	2 MP HD Mobile PTZ Camera
Camera	Image Sensor	1/2.8" Progressive Scan CMOS
	Image Quality	1080P(1920x 1080)
	Zoom	32X Optical Zoom , 16X Digital Zoom
	Focus Length	f=4.3~129 mm
	Lens	F1.6 ~ F3.5
	View Angle	61.4 (Wide)~ 2.9° (Tele)
	Min Distance	10cm~INF
	S/N Ratio	> 52dB
	Day & Night Mode	Auto ICR
	White Balance	Auto/Manual
	Focus Mode	Auto/Manual/One AF
	Gain	Auto/Manual
	Electronic Shutter	1/1 ~ 1/10,000
	Min. Illumination	Color 0.005 lux (F1.6, AGC ON), B/W 0 Lux (IR ON)
	WDR	Support
DNR	3D	
Mirror	Horizontal, Vertical, Center	
Images	Image Size	2MP 1080P(1920*1080)
	Video Compression	H.265/H.264 Main Profile, MJPEG/JPEG Baseline
	Dual Stream	Support
	Resolution	Main Stream: 1920×1080 1080P/ 1280×960 960P/ 1280×720 720P Sub Stream: 704×576, D1/352×288 CIF
	Audio	G.711
Network	ONVIF	Support
	Protocols	TCP/IP, HTTP, DHCP, DDNS, RTP, RTSP, PPPoE, UPnP, FTP, IPv6 , SIP, SRTP
PTZ	Pan Preset Speed	100°/S
	Tilt Preset Speed	80°/S
	Pan Adjust Speed	0°—60°/S
	Tilt Adjust Speed	0°—40°/S
	Pan Angle	360°
	Tilt Angle	-90°—+90°
	Preset/Pattern	256, 6 Line
	Video Output	RS485, 16 Protocols, Baud Rate: 2400Bps-19200Bps Optional
General	Working Humidity	<90%
	Protection Level	IP66
	Working Conditions	-30°C ~ 55°C
	Power Supply	DC12V ±20% (50VA)
	Impact Requirements	≥4G

	Wiper	Support
	Installation	Upon Different Application
	Dimensions (mm)	375x240x210mm
	Weight	6kg

Application For Police Cars/ Fire Emergency Command / Emergency Command System / Mobile Patrol Highways / Urban Management Law Enforcement / Special Vehicle Mobile Inspection

DIMENSIONS (Unit : mm)

