

# IT-3295SLG-PTZ-HD-2MP

## 2.0 Megapixel HD IR Laser Speed Dome Camera

### FEATURES

- Sony Ultra Sensor.
- Built in 2 Megapixel HD1080P, 32X Optical Zoom.
- First Patent of Out Cool Air Circulation to Sink the Heat Technology.
- First Patent of Video Analysis Light-adjustment Technology.
- The Highly Power Array LEDs with IR Laser Range Up To 300 Meters
- Unique Composite Lens Design, To Enhance Night Vision Effect
- Automatic Defrost & Defog (Manual Operation)
- Built-in 8 Cruise Tracks & 4 Pattern Tours
- Auto Tracking For Unman Duty Surveillance
- IP66/ Level 2 Lightning Protection, 4000V Anti-surges Design.
- Built-in Power, Wall Mounted Bracket Design
- Power Supply Box Outdoor Design, To Make It Convenient For Maintenance On Site (Configuration Optional).



### SPECIFICATIONS

Mode No.	<b>IT-3295SLG-PTZ-HD-2 MP</b>
Sensor	1/2.8" Sony Progressive Scan CMOS
Effective Pixels	1080P(1920*1080)
Zoom	32X Optical, 16X Digital
Focus Length	F=4.3~137.6mm
Iris	F1.6~F3.5
Horizontal View Angle	61.4°(wide angle)~2.9°(farthest end)
Day/ Night	Automatic / Multicolor / Monochrome
Focus Mode	Automatic/ Manual
S/N Ratio	> 52dB
BLC	OFF/ ON
White Balance	Automatic/ Manual
Electronic Shutter	1/1 s~1/30,000 s
Gain Control	Automatic/ Manual
Min illumination	Multi-color 0.005Lux @(F1.6, AGCON) /Monochrome 0.003Lux @(F1.6, AGCON)
WDR	Support
Max Image Size	1920×1080
Video Compression	H.265/H.264 Main Profile, MJPEG/JPEG Baseline
Dual Stream	1080P
Heartbeat	Support
Security Mechanism	Password Protection, Multi User Access Controlled
Communications Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, UPnP, SNMP, FTP, 802.1x, QoS, HTTPS, IPv6(SIP, SRTP), ONVIF
Interface	1*Network Interface, 1*Power Input
IR Laser Distance	300m
IR Lamp Control	Automatic /Manual / Camera

IR Lamp Consumption	18W
Pan Speed	Pan Speed: 0.01~360°/s, Speed Settable; Pan Preset Speed: 360°/s
Tilt Speed	Tilt Speed: 0.01~220°/s, Speed Settable; Tilt Preset Speed: 220°/s
Rotation	Pan: 360° Continuous Rotation; Tilt: -10°~90° Auto Flip
Preset	256 presets
Auto Scan	8 groups, Boundaries & Scan Speed Settable
Auto Cruise	8 groups, each with 32 presets with settable time interval
Pattern Tour	4 groups, each with 500 instructions
Video Analysis	Support
Alarm	1CH I/O
Audio	1CH I/O
Auto Track	Support
Packaged Structure With Pendant-mounting	Non-support
OSD Menu	English
Power Box	Configuration Optional
Heat Dispersion Structure	Out Cool Air Circulation to Sink the Heat Technology
Supply Voltage	DC12V±10%
Protection Level	IP66/ Level 2 Lightning Protection, 4000V Anti-surges Design
Working Temperature	-30°C ~ 55°C
Working Humidity	<90%, No Condensation
Consumption	Max. 38W
Weight	5.8Kg
Accessories	Wall-mount Bracket, DC12V Power Supply

## DIMENSIONS (Unit : mm)

