

IT-3211MP-HD-1MP

ATM HD Network Pinhole Camera

FEATURES

- Support HDTV Full Real-Time HD Picture Quality Transmission
- Support Onvif 2.4X Protocol
- Support Multiple Code Stream, 3D-DNR, Defogging, Motion Detection, WDR, Intelligent Functions
- Support Audio Input / Output, Mobile Surveillance



SPECIFICATIONS

Model	Model No.	IT-3211MP-HD-1MP
	Type	1.3 MP ATM HD Network Camera
Camera	Image Sensor	1/2.8" Sony Exmor Progressive Scan CMOS Sensor
	Min. Illumination	Color 0.05Lux@F1.2; B/W 0.005Lux@F1.2;
	Lens	3.7mm Pinhole
	Electronic Shutter	1 / 25 ~ 1 / 10000
	DNR	3D-DNR
	S/N Ratio	≥50db (AGC OFF)
	WDR	≥120db
	BLC	Support
Images	Video Compression	H.265/H.264 Baseline/Main Profile/High Profile
	Code Stream	CBR/ VBR/ LBR
	Frame Rate	1280*1024, 1-25(30)FPS/S; 1280*960, 1-25(30)FPS/S; 1280*720, 1-25(30)FPS/S
	Image Setting	Adjustable Image Format, Standard, Bit Rate, Brightness, Contrast, Saturation, Sharpness, White Balance, Image Flip and Mirror; OSD Information Overlay; Image Rotation
	Intelligent Features	Intelligent Code Stream, Intelligent Video Mask, Intelligent Out-of Focus Detection
	Protocol	IPv4, TCP/IP, UDP, HTTP, DHCP, RTP/RTCP/RTSP, FTP, UPnP, DDNS, NTP, IGMP, ICMP
	Compatible Protocol	Onvif
Port	Audio Port	1CH Audio Input, 1CH Audio Output
	Mobile Surveillance	Support
General	Working Temperature & Humidity	-20°C ~ 55°C, 20-80% RH (Non-Condensing)
	Power Supply	DC12V ±10%
	Dimensions (mm)	30(L) x30(W) x32(D)mm
	Weight (with Package)	180g

DIMENSIONS (Unit: mm)

