

IT-3212MP-HD-2MP

ATM HD Network Pinhole Camera

FEATURES

- Support HDTV Full Real-Time HD Picture Quality Transmission
- Support Onvif 2.4X Protocol
- Support Multiple Code Stream, 3D-DNR, Defogging, Motion Detection, WDR, Intelligent Functions
- Support Audio Input / Output, Support TF card, Mobile Surveillance



SPECIFICATIONS

Model	Model No.	IT-3212MP-HD-2MP
	Type	2 MP ATM HD Network Camera
Camera	Image Sensor	1/2.8" Sony Exmor Progressive Scan CMOS Sensor
	Min. Illumination	Color 0.05Lux@F1.2;B/W 0.005Lux@F1.2;
	Lens	3.7mm Pinhole
	Electronic Shutter	1 / 25 ~ 1 / 10000
	DNR	3D DNR
	S/N Ratio	≥50db (AGC OFF)
	WDR	≥120db
	BLC	Support
Images	Video-Compression	H.265/H.264 Baseline/Main Profile/High Profile
	Code Stream	CBR/ VBR/ LBR
	Frame Rate	1920*1080, 1-25(30)fps ; 1280*720, 1-25(30)fps
	Image Setting	Adjustable image format, standard, bit rate, brightness, contrast, saturation, sharpness, white balance, image flip and mirror; OSD information overlay; image rotation
	Intelligent Features	Intelligent Code Stream, Intelligent Video Mask, intelligent out of focus detection, intelligent control switch
	Protocol	IPv4, TCP/IP, UDP, HTTP, DHCP, RTP/RTCP/RTSP, FTP, UPnP, DDNS, NTP, IGMP, ICMP
	Compatible Protocol	Onvif
Port	Audio Port	1CH Audio Input, 1CH Audio Output
	TF card	Support
	Mobile Surveillance	Support
General	Working Temperature & Humidity	-20°C ~ 55°C, 20-80% RH (Non-Condensing)
	Power	DC12V ±10%
	Dimensions (mm)	43mm(L)*31mm(W)*29mm(D)
	Weight (with package)	175g

DIMENSIONS (unit : mm)

