

IT-5212MP-HD-2MP

Ultra WDR Starlight ATM HD Pinhole Camera

FEATURES

- Support HDTV Full Real-Time HD Picture Quality Transmission
- Support Onvif 2.4X Protocol
- Support Multiple Code Stream, 3D-DNR, Defogging, Motion Detection, WDR, Intelligent Functions
- Support Audio Input / Output, Support TF card, Mobile Surveillance



SPECIFICATIONS

Model	Model No.	IT-5212MP-HD-2MP
	Type	2 MP Ultra WDR ATM HD Network Camera
Camera	Image Sensor	1/2.8" Sony Exmor Progressive Scan CMOS Sensor
	Min. Illumination	Color 0.001Lux@F1.2; B/W 0.0001Lux@F1.2;
	Lens	3.7mm Pinhole
	Electronic Shutter	1 / 25 ~ 1 / 10000
	DNR	3D DNR
	S/N Ratio	≥50db (AGC OFF)
	WDR	≥140db
	BLC	Support
Images	Video Compression	H.265/H.264 /M-JPEG
	Code Stream	CBR/ VBR/ LBR
	Frame Rate	1920*1080, 1-25(30)fps
	Image Setting	Adjustable Image Format, Standard, Bit Rate, Brightness, Contrast, Saturation, Sharpness, White Balance, Image Flip and Mirror; OSD Information Overlay; Image Rotation
	Intelligent Features	Intelligent Code Stream, Intelligent Video Mask, Intelligent Out-of Focus Detection, intelligent control switch
	Protocol	IPv4, TCP/IP, UDP, HTTP, DHCP, RTP/RTCP/RTSP, FTP, UPnP, DDNS, NTP, IGMP, ICMP
Port	Compatible Protocol	Onvif
	Audio Port	1CH Audio Input, 1CH Audio Output
	TF card	Support
General	Mobile Surveillance	Support
	Working Temperature & Humidity	-20°C ~ 55°C, 20-80% RH (Non-Condensing)
	Power Supply	DC12V ±10%
	Dimensions (mm)	30(L) x30(W) x33(D)mm
	Weight (with package)	190g

DIMENSIONS (unit : mm)

