

IT-9655MG-HD-2MP IT-9655AG-HD-2MP

2.0 Megapixel HD Network Starlight Vandal Proof Outdoor Dome Camera




FEATURES

- Starlight Low Illumination
- H.265/H.264/M-JPEG, Support Multiple Code Stream
- HDTV, 1080P Full Real-Time Transmission
- Support ONVIF, Built-in Auto Double Filter Switching Mechanism, True Day/Night
- Support 3D DNR, Mobile Surveillance, Vandal Proof IK10 & IP66 (Anti-Reflection, Scratch-Proof)
- Support WDR, DC12V /AC24V/POE



SPECIFICATIONS

Model	Model No.	IT-9655MG-HD-2MP	IT-9655AG-HD-2MP
	Type	2 Megapixel HD Network Starlight Vandal Proof Outdoor Dome Camera	
Camera	Sensor	1/2.8" Progress Scan CMOS	
	Resolution	Main Stream	1920*1080, 1-25(30) FPS; 1280*720, 1-25(30) FPS;
		Sub Stream	704*576, 1-25(30) FPS; 640*480, 1-25(30) FPS
	Min. Illumination	Color 0.005Lux@F1.2; B/W 0.0005Lux@F1.2	
	S/N Ratio	≥52db	
	WDR	≥120db	
	Electronic Shutter	1~ 1/10000 sec, Automatic	
	Lens	2.8-12mm Manual Zoom Lens	2.8-12mm 3MP Motorized Focus Lens
Day & Night	IR Cut Optical Filter		
Audio/Video Setting	Video Compression	H.265/ H.264/ M-JPEG, Support Multiple Code Stream	
	Code Stream	32Kbps-16Mbps, Support CBR/VBR	
	Video Adjustment	Brightness/ Contrast / Chroma/ Saturation/ Sharpness / GAMMA	
	Intelligent Features	Intelligent Code Stream, Video Mask, Out-of-focus Detection, Intelligent Switch Control	
	Image Flip	Horizontal, Vertical, Horizontal & Vertical	
	Motion Detection	Support	
	Privacy Mask	Support	
	3D DNR	High/Medium/Low	
OSD Setting	Support Channel Name, Date Time, Code Stream Overlay		
Network	Interface	10/100 M Ethernet (RJ-45)	
	Protocol	TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, SMTP, UPNP	
	ONVIF	Onvif 2.4	
	Access Control	Administer and Common User	
	Web Browser	IE 6.0 and Above	
	Max. User Number	≤10	
General	CVBS/BNC	Support	
	Audio I/O	Support	
	Alarm I/O	Support	
	RS485	Support	
	TF Card	Support	
	Mobile Surveillance	Support	
	IP Grade	IP 66	
	IK Grade	IK 10	
	Working Conditions	-20°C ~ 60°C; 10% to 90%, (Non-Condensing)	
	Power Supply	POE /DC12V /AC24V ±10%	
	Dimensions (mm)	150(Φ)x100(H)mm	
Weight (with package)	980g		

For Financial, Prison, Supermarket, Telecom, Government, School, Airport, Factory, Hotel and Other Indoor /Outdoor Places.

DIMENSIONS (Unit : mm)

