IT-9925G-HD-2MP

2.0 Megapixel HD Network Ultra Starlight Box Camera

ONVIF

FEATURES

● H.265/H.264/M-JPEG, Support Multiple Code Stream

● Built-in Auto Double Filter Switching Mechanism, True Day/Night

● Support WDR, 3D-MCTF DNR and the ROI Compression Interested Area

● Support Corridor Mode, Adapt to the Special Area Show in Long and Narrow Corridor

● The Power Interface using Error Prevention Design, Avoid Mistaken Insertion or Reverse Damage to the Camera Circuit.

● Support ONVIF, HDMI Output, DC12V/AC24V/POE

SPECIFICATIONS

Model	Model No.	**IT-9925G-HD-2MP**
	Type	2 Megapixel HD Network Ultra Starlight Box Camera
Camera	Sensor	1 / 1.8'' Sony Progress Scan CMOS
	Min. Illumination	Color 0.001Lux@F1.2; B/W 0.0001Lux@F1.2
	Electronic Shutter	1 / 25 ~ 1 / 10000
	Lens Interface	C/CS
	DNR	3D DNR
	S/N Ratio	≥52db
	Aperture Type	DC Drive, Support Auto/ Manual/ Fixed Lens
	WDR Range	≥120db
	BLC	Support
Image	Video Compression	H.265/H.264 /MJPEG, Frame Rate Adjustable
	Code Stream	VBR/ CBR/ LBR
	Frame Rate	1920*1080, 1-25(30) FPS; 1280*720, 1-25(30) FPS;
	Image Setting	Adjustable Image Format, Standard, Code Rate, Brightness, Contrast, Saturation, Sharpness, White Balance, Image Flip and Mirror (Passage Mode) 4A Auto Control, OSD Information Overlay; Image Flip
	Intelligent Features	Intelligent Code Stream, Video Mask, Out-of-focus Detection, Intelligent Switch Control
	Protocol	IPv4, TCP/IP, UDP, HTTP, DHCP, RTP/RTCP/RTSP, FTP, UPnP, DDNS, NTP, IGMP, ICMP
	Compatible	Support ONVIF
Interfaces	Audio Interface	3.5mm Microphone/ Line in, External Active Microphone or Line Input
	Communication Interface	1* RJ45 10Base-T/100Base-TX
	Alarm I/O	1CH Input, 1CH Output
	Audio I/O	Support
	TF Card	Support
	HDMI	Support
	RS485	Support
	BNC	Support
	Mobile Surveillance	Support
General	Working Conditions	-20℃~ 60℃, 20-80% RH (non-condensing)
	Power Supply	POE /DC12V /AC24V ±10%
	Dimensions (mm)	152 (L)x81(W)x54(H)mm （Without Lens）
	Weight (with Package)	820g

For Financial, Supermarket, Telecom, Government, School, Airport, Factory, Hotel, Train Station and Other Indoor/ outdoor Places.

DIMENSIONS (Unit : mm)

143

152

54

81