

# IT-9646MG-HD-3MP IT-9646AG-HD-3MP



## 3.0 Megapixel HD Network Starlight Bullet Camera



### FEATURES

- Starlight Low Illumination
- H.265/H.264/M-JPEG, Support Multiple Code Stream
- HDTV 3MP Full Real-Time Transmission
- Support ONVIF, Built-in Auto Double Filter Switching Mechanism, True Day/Night
- Support 3D DNR, Mobile Surveillance, Weatherproof IP66
- Support WDR, DC12V/AC24V/POE



### SPECIFICATIONS

Model	Model No.		IT-9646MG-HD-3MP	IT-9646AG-HD-3MP	
		Type		3 Megapixel HD Network Starlight Bullet Camera	
Camera	Sensor		1/2.8" Progress Scan CMOS		
	Resolution	Main Stream	2048*1536, 1-25(30)FPS; 1920*1080, 1-25(30)FPS; 1280*720, 1-25(30)FPS		
		Sub Stream	704*576, 1-25(30)FPS; 640*480, 1-25(30)FPS		
	Min. Illumination		Color 0.001Lux@F1.2, B/W 0.0001Lux@F1.2		
	IR Distance		////////////////////		
	S/N Ratio		≥52db		
	WDR		≥120db		
	Electronic Shutter		1~ 1/10000 sec, Automatic		
	Lens		2.8-12mm Manual Zoom Lens	2.8-12mm 3MP Motorized Focus	
	Day & Night		IR Cut Optical Filter		
Audio/Video Setting	Video Compression		H.265/H.264/M-JPEG, Support Multiple Code Stream		
	Code Stream		32Kbps-16Mbps, Support CBR/VBR		
	Video Adjustment		Brightness/ Contrast / Chroma/ Saturation/ Sharpness / GAMMA		
	Intelligent Features		Intelligent Code Stream, Video Mask, Out-of-focus Detection, Intelligent Switch Control		
	Image Flip		Horizontal, Vertical, Horizontal & Vertical		
	Motion Detection		Support		
	Privacy Mask		Support		
	3D DNR		High/Medium/Low		
Network	OSD Setting		Support Channel Name, Date Time, Code Stream Overlay		
	Interface		10/100 M Ethernet (RJ-45)		
	Protocol		TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, SMTP, UPNP		
	ONVIF		Onvif 2.4		
	Access Control		Administer and Common User		
	Web Browser		IE 6.0 and Above		
Interfaces	Max. User Number		≤10		
	CVBS/BNC		Support		
	Audio I/O		Support		
	Alarm I/O		Support		
	RS485		Support		
General	Mobile Surveillance		Support		
	IP Grade		IP 66		
	Working Conditions		-20°C ~ 60°C; 10% to 90% (Non-Condensing)		
	Power Supply		DC12V/AC24V/POE		
	Dimensions (mm)		315(L) x90(W)x100(H)mm		
Weight (with package)		840g			

**For Financial, Prison, Supermarket, Telecom, Government, School, Airport, Factory, Hotel and Other Indoor /Outdoor Places.**

**DIMENSIONS** (Unit : mm)

