

IT-9656MG-HD-3MP IT-9656AG-HD-3MP

3.0 Megapixel HD Network Starlight Vandal Proof Outdoor Dome Camera

ONVIF



FEATURES

- Starlight Low Illumination
- H.265/H.264/M-JPEG, Support Multiple Code Stream
- HDTV 3MP Full Real-Time Transmission
- Support ONVIF, Built-in Auto Double Filter Switching Mechanism, True Day/Night
- Support 3D DNR, Mobile Surveillance, Anti-Reflection, Scratch-Proof
- Support WDR, DC12V/AC24V/POE



SPECIFICATIONS

Model	Model No.	IT-9656MG-HD-3MP	IT-9656AG-HD-3MP
	Type	3 Megapixel HD Network Starlight Vandal Proof Outdoor Dome Camera	
Camera	Sensor	1/2.8" Progress Scan CMOS	
	Resolution	Main Stream	2048*1536, 1-25(30)FPS; 1920*1080, 1-25(30)FPS; 1280*720, 1-25(30)FPS
		Sub Stream	704*576, 1-25(30)FPS; 640*480, 1-25(30)FPS
	Min. Illumination	Color 0.001Lux@F1.2; B/W 0.0001Lux@F1.2	
	S/N Ratio	≥52db	
	WDR	≥120db	
	Electronic Shutter	1~ 1/10000 sec.	
	Lens	2.8-12mm Manual Zoom Lens	2.8-12mm HD Motorized Focus Lens
Day & Night	IR Cut Optical Filter		
Audio/Video Setting	Video Compression	H.265/H.264/M-JPEG, Support Multiple Code Stream	
	Code Stream	32Kbps-16Mbps, Support CBR/VBR	
	Video Adjustment	Brightness/ Contrast / Chroma/ Saturation/ Sharpness / GAMMA	
	Intelligent Features	Intelligent Code Stream, Video Mask, Out-of-focus Detection, Intelligent Switch Control	
	Image Flip	Horizontal, Vertical, Horizontal & Vertical	
	Motion Detection	Support	
	Privacy Mask	Support	
	3D DNR	High/Medium/Low	
	OSD Setting	Support Channel Name, Date Time, Code Stream Overlay	
	Network	Interface	10/100 M Ethernet (RJ-45)
Protocol		TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, SMTP, UPNP	
ONVIF		Onvif 2.4	
Access Control		Administer and Common User	
Web Browser		IE 6.0 and Above	
Max. User Number		≤10	
Interfaces	CVBS/BNC	Support	
	Audio I/O	Support	
	Alarm I/O	Support	
	RS485	Support	
	TF Card	Support	
	Mobile Surveillance	Support	
General	IP Grade	IP 66	
	IK Grade	IK 10	
	Working Conditions	-20°C ~ 60°C; 10% to 90% (Non-Condensing)	
	Power Supply	DC12V/AC24V/POE	
	Dimensions (mm)	150(Φ)x100(H)mm	
Weight (with package)	980g		

For Financial, Prison, Supermarket, Telecom, Government, School, Airport, Factory, Hotel and Other Indoor /Outdoor Places.

DIMENSIONS (Unit : mm)

