

IT-1646FIG30-HD-4MP IT-1646MIG30-HD-4MP IT-1646AIG30-HD-4MP

4.0 Megapixel HD Network IR 30M Bullet Camera



FEATURES

- H.265/H.264/M-JPEG, Support Multiple Code Stream
- HDTV, 3MP Full Real-Time / 4MP Non Real-Time Transmission
- Support ONVIF, Built-in Auto Double Filter Switching Mechanism, True Day/Night
- Support 3D DNR, Mobile Surveillance, IR 30M & 42pcs IR LED, Weatherproof IP66
- Support WDR, DC12V/AC24V/POE



SPECIFICATIONS

Model	Model No.	IT-1646FIG30-HD-4MP	IT-1646MIG30-HD-4MP	IT-1646AIG30-HD-4MP
	Type	4.0 Megapixel HD Network IR Bullet Camera		
	Sensor	1/3"Progress Scan CMOS		
Camera	Resolution	Main Stream	2592*1520, 1-15FPS; 2040*1536, 1-25(30)FPS; 1920*1080, 1-25(30)FPS	
		Sub Stream	704*576, 1-25(30)FPS; 640*480, 1-25(30)FPS	
	Min. Illumination	Color 0.1Lux@F1.2; B/W 0Lux@F1.2 (IR ON)		
	IR Distance	IR 30M, 42pcs IR LED		
	S/N Ratio	≥52db		
	WDR	≥120db		
	Electronic Shutter	1~ 1/10000 sec, Automatic		
	Lens	6mm(3.6/8/12mm Optional) Fixed Lens	2.8-12mmManual Zoom Lens	2.8-12mm Motorized Focus Lens
Day & Night	IR Cut Optical Filter			
Audio/Video Setting	Video Compression	H.265/ H.264/ M-JPEG, Support Multiple Code Stream		
	Code Stream	32Kbps-16Mbps, Support CBR/VBR		
	Video Adjustment	Brightness/ Contrast / Chroma/ Saturation/ Sharpness / GAMMA		
	Intelligent Features	Intelligent Code Stream, Video Mask, Out-of-focus Detection, Intelligent Switch Control		
	Image Flip	Horizontal, Vertical, Horizontal & Vertical		
	Motion Detection	Support		
	Privacy Mask	Support		
	3D DNR	High/Medium/Low		
OSD Setting	Support Channel Name, Date Time, Code Stream Overlay			
Network	Interface	10/100 M Ethernet (RJ-45)		
	Protocol	TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, SMTP, UPNP		
	ONVIF	Support		
	Access Control	Administer and Common User		
	Web Browser	IE 6.0 and Above		
	Max. User Number	≤10		
Interfaces	CVBS	Support		
	Audio I/O	Support		
	Alarm I/O	Support		
	RS485	Support		
	Mobile Surveillance	Support		
General	IP Grade	IP 66		
	Working Conditions	-20°C ~ 60°C; 10% to 90% (Non-Condensing)		
	Power Supply	DC12V/AC24V/POE ±10%		
	Dimensions (mm)	315(L) x90(W)x100(H)mm		
	Weight (with package)	840g		

For Financial, Prison, Supermarket, Telecom, Government, School, Airport, Factory, Hotel and Other Indoor /Outdoor Places.

DIMENSIONS (Unit : mm)

