

IT-1656MIG-A-HD-4MP IT-1656AIG-A-HD-4MP

4.0 Megapixel HD Network IR Vandal Proof Outdoor Dome Camera



FEATURES

- H.265/H.264/M-JPEG, Support Multiple Code Stream
- HDTV, Support 4 Megapixel Full Real Time Transmission
- Support ONVIF, Built-in Auto Double Filter Switching Mechanism, True Day/Night
- Support 3D DNR, Mobile Surveillance, IR 30M, Vandal Proof IK10 & IP66 (Anti-Reflection, Scratch-Proof)
- Support WDR, DC12V/AC24V/POE



SPECIFICATIONS

Model	Model No.		IT-1656MIG-A-HD-4MP	IT-1656AIG-A-HD-4MP	
		Type		4.0 MP HD Network IR Vandal Proof Outdoor Dome Camera	
Camera	Sensor		1/3" Progress Scan CMOS		
	Resolution	Main Stream	2592*1520, 1-25(30)FPS; 2040*1536, 1-25(30)FPS; 1920*1080, 1-25(30)FPS		
		Sub Stream	704*576, 1-25(30)FPS; 640*480, 1-25(30)FPS		
	Min. Illumination		Color 0.1Lux@F1.2; B/W 0Lux@F1.2 (IR ON)		
	IR Distance		IR 30M, 24pcs IR LED		
	S/N Ratio		≥52db		
	WDR		≥120db		
	Electronic Shutter		1~ 1/10000 sec.		
	Lens		2.8-12mm Manual Zoom Lens	2.8-12mm HD IR 3MP Motorized	
	Day & Night		IR Cut Optical Filter		
Audio/Video Setting	Video Compression		H.265/H.264/M-JPEG, Support Multiple Code Stream		
	Code Stream		32Kbps-16Mbps, Support CBR/VBR		
	Video Adjustment		Brightness/ Contrast / Chroma/ Saturation/ Sharpness / GAMMA		
	Intelligent Features		Intelligent Code Stream, Video Mask, Out-of-focus Detection, Intelligent Switch Control		
	Image Flip		Horizontal, Vertical, Horizontal & Vertical		
	Motion Detection		Support		
	Privacy Mask		Support		
	3D DNR		High/Medium/Low		
	OSD Setting		Support Channel Name, Date Time, Code Stream Overlay		
Network	Interface		10/100 M Ethernet (RJ-45)		
	Protocol		TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, SMTP, UPNP		
	ONVIF		Onvif 2.4		
	Access Control		Administer and Common User		
	Web Browser		IE 6.0 and Above		
	Max. User Number		≤10		
Interfaces	CVBS/BNC		Support		
	Audio I/O		Support		
	Alarm I/O		Support		
	RS485		Support		
	TF Card		Support		
	Mobile Surveillance		Support		
General	IP Grade		IP 66		
	IK Grade		IK 10		
	Working Conditions		-20°C ~ 60°C; 10% to 90% (Non-Condensing)		
	Power Supply		POE /AC24V/DC12V ±10%		
	Dimensions (mm)		150(Φ)x100(H)mm		
Weight (with package)		980g			

For Financial, Prison, Supermarket, Telecom, Government, School, Airport, Factory, Hotel and Other Indoor /Outdoor Places.

DIMENSIONS (Unit : mm)

