

IT-113PRI-HD-1MP IT-123PRI-HD-2MP

HD IR IP Dome Camera



FEATURES

- HDTV Image Quality, Support 1024P/1080P Real-Time
- Support Onvif
- Support 3D DNR, DC12V
- Mobile Surveillance (Optional)

SPECIFICATIONS

Model	Model No.	IT-113PRI-HD-1MP	IT-123PRI-HD-2MP
	Type	1.3 Megapixel HD IR Dome camera	2 Megapixel HD IR Dome camera
	Image Sensor	1/3"Progress Scan CMOS	1/2.8" Progress Scan CMOS
Camera	Resolution	Main Stream	1280*1024, 1-25(30)Fps 1280*960, 1-25(30)Fps 1280*720, 1-25(30)Fps
		Sub Stream	1920*1080, 1-25(30)Fps 1280*720, 1-25(30)Fps
	Min. Illumination	Color 0.01Lux@F1.2; B/W: 0Lux@F1.2 (IR ON)	Color 0.01Lux@F1.2; B/W: 0Lux@F1.2 (IR ON)
	S/N Ratio	≥50db (AGC OFF)	
	WDR	80db	
	Electronic Shutter	1~ 1/10000 sec., Auto	
	Lens	2.8/3.6/6mm	
	Day/Night	EI (ICR Optional)	
	IR Distance	15m/24pcs Led	
	Audio/ Video Settings	Compression	H.264 (Baseline, Main Profile)/M-JPEG
Code Stream		32Kbps-16Mbps Adjustable, Support CBR/VBR The Code Rate& Frame Rate of LAN & WAN can be respectively set upon the same code stream	
Video Adjustment		Brightness/Contrast/Chromatic /Saturation/ Sharpness /GAMMA	
Electronic Shutter		1/25~1/8000	
Image Flip		Support	
Motion Detection		Support	
Privacy Mask		Support	
3D DNR		High/ Middle/ Low	
OSD	Support Channel Name , Date and Stream Overlay, the position adjustable		
Network	Interface	10/100 M Ethernet (RJ-45)	
	Protocol	TCP/IP、UDP、RTP、RTSP、RTCP、HTTP、DNS、DDNS、DHCP、FTP、NTP、PPPOE、SMTP、UPNP	
	ONVIF	Support	
	Access Control	Administer and Common User	
	Web Browser	IE 6.0 and above	
	Max. User Number	≤10	
General	Audio Input / Output	Optional	
	Adjustment Range	3-Axis Rotation	
	Mobile Surveillance	Support	
	Working Condition	-20°C ~ 50°C; 10% to 90%, Non-condensing	
	Power Supply	DC12V	
	IP Rating	IP60	
	Dimensions (mm)	93(Φ)X80(H)MM	
Weight (with package)	195g		

DIMENSIONS (Unit : mm)

