

# IT-214PRI-HD-1MP IT-224PRI-HD-2MP

## HD IR IP Bullet Camera



### FEATURES

- HDTV Image Quality, Support 720P/1024P/1080P/ 3 Megapixel Real-Time
- Support Onvif
- Support 3D DNR, DC12V, Weatherproof IP66
- Support Mobile Surveillance

### SPECIFICATIONS

Model	Model No.	IT-214PRI-HD-1MP	IT-224PRI-HD-2MP
	Type	1.3 Megapixel HD IR Bullet Camera	2 Megapixel HD IR Bullet Camera
	Image Sensor	1/3"Progress Scan CMOS	1/2.8" Progress Scan CMOS
Camera	Resolution	Main Stream	1280*1024, 1-25(30)Fps 1280*960, 1-25(30)Fps 1280*720, 1-25(30)Fps
		Sub Stream	720*576, 1-25(30)Fps; 640*480, 1-25(30)Fps
	Min. Illumination	Color 0.01Lux@F1.2; B/W 0Lux@F1.2 (IR ON)	
	S/N Ratio	≥50db(AGC OFF)	
	WDR	≥80db	
	Electronic Shutter	1~ 1/10000 sec., Auto	
	Lens	3.6/4/6mm	
	Day/Night	EI (ICR Optional)	
	IR Distance	30m/3pcs Led Array	
Audio/video Settings	Compression	H.264 (Baseline, Main Profile) /M-JPEG	H.265/H.264 (Baseline, Main Profile) /M-JPEG
	Code Stream	32Kbps-16Mbps Adjustable, Support CBR/VBR The Code Rate& Frame Rate of LAN & WAN can be respectively set upon the same code stream	
	Video Adjustment	Brightness/Contrast/Chromatic /Saturation/ Sharpness /GAMMA	
	Electronic Shutter	1/25~1/8000	
	Image Flip	Support	
	Motion Detection	Support	
	Privacy Mask	Support	
	3D DNR	High/ Middle/ Low	
	OSD	Support Channel Name , Date and Stream Overlay, the position adjustable	
Network	Interface	10/100 M Ethernet (RJ-45)	
	Protocol	TCP/IP、 UDP、 RTP、 RTSP、 RTCP、 HTTP、 DNS、 DDNS、 DHCP、 FTP、 NTP、 PPPOE、 SMTP、 UPNP	
	ONVIF	Support	
	Access Control	Administer and Common User	
	Web Browser	IE 6.0 and above	
	Max. User Number	≤10	
General	Audio Input / Output	Optional	
	Adjustment Range	3-Axis Rotation	
	Mobile Surveillance	Optional	
	Working Condition	-10°C ~ 50°C; 10% to 90%, Non-condensing	
	Power Supply	DC12V,POE optional	
	IP Rating	IP66	
	Dimensions (mm)	66.8(W)X155.33(W) mm	
	Weight (with package)	450g	

**DIMENSIONS** (Unit : mm )

