

# IT-714PRI-HD-1MP IT-724PRI-HD-2MP IT-734PRI-HD-3MP

## HD IR IP Bullet Camera

### FEATURES

- HDTV Image Quality, Support 1024P/1080P/ 3 Megapixel Real-Time
- Support Onvif, GBT28181
- Support 3D DNR, DC12V
- Mobile Surveillance (Optional), IP66



### SPECIFICATIONS

Model	Model No.	IT-714PRI-HD-1MP	IT-724PRI-HD-2MP	IT-734PRI-HD-3MP	
	Type	1.3 Megapixel HD IR Bullet Camera	2 Megapixel HD IR Bullet Camera	3 Megapixel HD IR Bullet Camera	
Camera	Image Sensor	1/3"Progress Scan CMOS	1/2.8" Progress Scan CMOS	1/3" Progress Scan CMOS	
	Resolution	Main Stream	1280*1024 1-25(30)Fps 1280*960 1-25(30)Fps 1280*720 1-25(30)Fps	1920*1080 1-25(30)Fps 1280*720 1-25(30)Fps	2592*1520 1~15 Fps 2048*1520 1~25(30)Fps
		Sub Stream	720*576, 1-25(30)Fps; 640*480, 1-25(30)Fps		
	Min. Illumination	Color 0.01Lux@F1.2; B/W0. 0Lux@F1.2 (IR ON)			
	S/N Ratio	≥50db(AGC OFF)			
	WDR	Optional			
	Electronic Shutter	1~ 1/10000 sec., Auto			
	Lens	3.6/6/8mm			
	Day/Night	EI (ICR Optional)			
	IR Distance	40m/2pcs Led Array			
Audio/Video Settings	Compression	H.264 (Baseline, Main Profile)/M-JPEG	H.265/H.264 (Baseline, Main Profile)/M-JPEG		
	Code Stream	32Kbps-16Mbps Adjustable, Support CBR/VBR The Code Rate & Frame Rate of LAN & WAN can be respectively set upon the same code stream			
	Video Adjustment	Brightness/Contrast/Chromatic /Saturation/ Sharpness /GAMMA			
	Electronic Shutter	1/25~1/8000			
	Image Flip	Support			
	Motion Detection	Support			
	Privacy Mask	Support			
	3D DNR	High/ Middle/ Low			
	OSD	Support Channel Name , Date and Stream Overlay, the position adjustable			
Network	Interface	10/100 M Ethernet (RJ-45)			
	Protocol	TCP/IP、UDP、RTP、RTSP、RTCP、HTTP、DNS、DDNS、DHCP、FTP、NTP、PPPOE、SMTP、UPNP			
	ONVIF	Support			
	Access Control	Administer and Common User			
	Web Browser	IE 6.0 and above			
	Max. User Number	≤10			
General	Audio Input / Output	Optional			
	Adjustment Range	3-Axis Rotation			
	Mobile Surveillance	Support			
	Working Condition	-10°C ~ 50°C; 10% to 90%, Non-condensing			
	Power Supply	DC12V, POE optional			
	IP Rating	IP66			
	Dimensions (mm)	268.7(L)X108.4(W)X89.9(H)			
Weight (with package)	732g				

**DIMENSIONS** (Unit : mm)

