

IT-813PRI-HD-1MP IT-823PRI-HD-2MP IT-833PRI-HD-3MP

HD IR IP Vandal Proof Outdoor Dome Camera



FEATURES

- HDTV Image Quality, Support 1024P/1080P/ 3 Megapixel Real-Time
- Support Onvif
- Varifocal 2.8~12 mm lens, Auto Focus Optional
- Support 3D DNR, DC12V, Auto Focus Lens Optional
- Mobile Surveillance (Optional), Vandal Proof IK10, IP66

SPECIFICATIONS

Model	Model No.	IT-813PRI-HD-1MP	IT-823PRI-HD-2MP	IT-833PRI-HD-3MP	
	Type	1.3 Megapixel HD IR Dome camera	2.0 Megapixel HD IR Dome camera	3.0 Megapixel HD IR Dome camera	
Camera	Image Sensor	1/3"Progress Scan CMOS	1/2.8"Progress Scan CMOS	1/3"Progress Scan CMOS	
	Resolution	Main Stream	1280*1024, 1-25(30) Fps 1280*960, 1-25(30) Fps 1280*720, 1-25(30) Fps	1920*1080, 1-25(30) Fps 1280*720, 1-25(30) Fps	2592*1520, 1~15 Fps 2048*1520, 1~25(30) Fps
		Sub Stream	720*576, 1-25(30) Fps; 640*480, 1-25(30) Fps		
	Min. Illumination	Color 0.01Lux@F1.2; B/W: 0Lux@F1.2 (IR ON)			
	S/N Ratio	≥50db (AGC OFF)	≥52db (AGC OFF)		
	WDR	≥80db			
	Electronic Shutter	1~ 1/10000 sec., Auto			
	Lens	2.8~12mm			
	Day/Night	EI (ICR Optional)			
	IR Distance	25m, 24pcs Led			
Audio/Video Settings	Compression	H.264/M-JPEG	H.265/H.264/M-JPEG		
	Code Stream	32Kbps-16Mbps Adjustable, Support CBR/VBR The Code Rate & Frame Rate of LAN & WAN can be respectively set upon the same code stream			
	Video Adjustment	Brightness/ Contrast/ Chromatic / Saturation/ Sharpness / GAMMA			
	Electronic Shutter	1/25~1/8000			
	Image Flip	Support			
	Motion Detection	Support			
	Privacy Mask	Support			
	3D DNR	High/ Middle/ Low			
	OSD	Support Channel Name , Date and Stream Overlay, the position adjustable			
Network	Interface	10/100 M Ethernet (RJ-45)			
	Protocol	TCP/IP、UDP、RTP、RTSP、RTCP、HTTP、DNS、DDNS、DHCP、FTP、NTP、PPPOE、SMTP、UPNP			
	ONVIF	Support			
	Access Control	Administer and Common User			
	Web Browser	IE 6.0 and above			
	Max. User Number	≤10			
General	Audio Input / Output	Optional			
	Adjustment Range	3-Axis Rotation			
	Mobile Surveillance	Support			
	Working Condition	-10°C ~ 50°C; 10% to 90%, Non-condensing			
	Power Supply	DC12V, POE optional			
	Vandal-proof	IK10			
	IP Rating	IP66			
	Dimensions (mm)	133(Φ)X100.3(H)MM			
Weight (with package)	576g				

DIMENSIONS (Unit : mm)

