

IT-1059FIG-HD-12MP

4K HD Network Panoramic IR Vandal-proof Dome Camera



FEATURES

- HDTV, Support 4K 8.0MP Full Real-time Transmission (4K 12MP Non-Real Time Transmission)
- Fish-eye Lens & Panoramic Multi-View with WDR
- Two-way Audio, ePTZ Control
- Alarm Action Diversification, Support Image Correction
- Support IR Cut Switch, IR Distance: 30M
- DC12V

SPECIFICATIONS

Model	Model No.	IT-1059FIG-HD-12MP
	Type	4K HD Network Panoramic Vandal-proof IR Dome camera
Camera	Sensor	1/1.7" CMOS
	Resolution	Effective 8.8MP (4096*2160), 25/30Fps; 12MP, 4K3K (4000x3000), 15Fps;
	Electronic Shutter	1/10000s to 1/25s; Manual or Automatic
	Min. Illumination	0.002Lux@(Color), 0.0002Lux@F2.0(B/W), 0Lux(IR ON)
	IR Distance	30 M
	PIR Sensor Distance	IR-CUT Auto Switch
	Scan	Progressive Scan
	DNR	3D DNR
	WDR	120dB
	S/N Ratio	> 52dB
	Gain control	Manual/Automatic
	White Balance	Manual/Automatic
	BLC	Support, Area setting Available
	HLC	Support
	Lens Mount	M12
	Lens IRIS	F2.0
	IRIS Control	Fixed
Zoom	Fixed	
FOV	Horizontal: ≥180°; Vertical: 87.3°	
Audio	Audio Input	1CH, RCA Input; 1CH Microphone Input

	Audio Output	1CH, RCA Output; 1CH Speaker Output
	Compression	G.711(ALAW)/MP2/G.711(MULAN)
	Code Rate	16K/24K/32K/40K/48K/56K/64K/128K/256K
Video	Compression Standard	H.265 MP, H.264 BP/MP/HP, MJPEG
	Code Rate	32 Kbps ~ 12Mbps
	Horizontal Resolution	>1500TVL
	Multi-streams	Fish-eye/Panoramic/ePTZ+Full D1+MJPEG Snapshot
	Video Code Rate	Under All Resolutions, it can in Full Frame Rate simultaneously Output Multi-Channel Video Streams, Frame Speed and Frame Rate are Adjustable
	View Mode	Ceiling, Wall, Desktop, 360° Fish-eye, 180° Panoramic and ePTZ
	Frame	Fish-eye: 2960x2960; Panoramic: 4608x1280, 2960x1480P; Panoramic +3ePTZ: 3840x2160P, 3200x2400P; 4ePTZ: 3200x2400P
Alarm	Alarm Input	1CH
	Alarm Linkage	Support No SD Card; SD Card No Space; SD Card Error; Network Disconnection; IP Conflict; Motion Detection; Video Mask
Feature	Image Setting	Brightness; Contrast; Sharpness; Saturation
	OSD Setting	Support Date Time, Channel Name, Location, Picture
	Heartbeat	Support
	Record Mode	Manual; Video Detection; Timing; Alarm, Priority from high to low: Manual/External Alarm/ Video Detection/ Timing
	Storage	Support Micro SD, Max to 128GB NAS FTP
	Max. Preview User Number	20
	Restore Defaults	One Key restore the default configuration
	User Management	Support Max 20 Users, Multiple User Right Management
	Security Mode	Authorized User Name and Password; Network Access Control
	Ultra-Low Stream	4M: 2~4Mbps
	Privacy Mask	Support
	Other Functions	Wide-angle Lens Distortion Correction, Gamma Compensation, Color Enhancement, One Key to Restore Factory Settings, Anti-flicker, Multi-streams, Heartbeat, Image Rotation, Privacy Zone Shelter, Watermark, Set Access Port
Interface	Network	1* 100/1000M Ethernet (RJ-45)
	Protocol	HTTP; TCP; ARP; RTSP; RTP; UDP; RTCP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; SNMP; UPnP; NTP
	Standard	ONVIF; GB/T28181
	Analog Output	1CH, Composite Analog Video Output, BNC (1.0Vp-p,75Ω)
General	Power Supply	DC12V
	Power Consumption	Max to 23W (IR ON, ABF, ICR Switch)
	Working Temperature	-30°C+60°C (-H: -40°~60°)
	Working Humidity	≤95%
	Protection Level	IP66; IK10
	Housing	Metal
	Dimension (mm)	Ø132mm×44mm
	Installation	Ceiling Mounted

For Financial, Prison, Supermarket, Telecom, Government, School, Airport, Factory, Hotel and Other Indoor Places.

DIMENSIONS (Unit: mm)

