

IT-3011MP-HD-1MP IT-3011MP-C-HD-1MP



ATM HD Network Pinhole Camera



FEATURES

- Support HDTV Full Real-Time HD Picture Quality Transmission
- Support Onvif 2.4X Protocol
- Support Multiple Code Stream, 3D-DNR, Defogging, Motion Detection, WDR, Intelligent Functions
- Support Audio Input / Output (IT-3011MP-C-HD-1MP), Mobile Surveillance

SPECIFICATIONS

Model	Model No.	IT-3011MP-HD-1MP	IT-3011MP-C-HD-1MP
	Type	1.3 MP ATM HD Network Camera	
Camera	Image Sensor	1/3" Sony Exmor Progressive Scan CMOS Sensor	1/2.9" Sony Exmor Progressive Scan CMOS Sensor
	Min. Illumination	Color0.1Lux@F1.2; B/W0.01Lux@F1.2;	Color0.05Lux@F1.2;
	Lens	3.7mm Pinhole	
	Electronic Shutter	1 / 25 ~ 1 / 10000	
	DNR	3D-DNR	
	S/N Ratio	≥50db (AGC OFF)	
	WDR	≥80db	≥120db
	BLC	Support	
Images	Video Compression	H.264 Baseline/Main Profile	H.265/H.264 Baseline/Main Profile/High
	Code Stream	CBR/ VBR/ LBR	
	Frame Rate	1280*960, 1-25FPS/S, 1280*720, 1-25FPS/S	1280*1024, 1-25(30)FPS/S, 1280*960, 1-25(30)FPS/S 1280*720, 1-25(30)FPS/S
	Image Setting	Adjustable Image Format, Standard, Bit Rate, Brightness, Contrast, Saturation, Sharpness, White Balance, Image Flip and Mirror; OSD Information Overlay; Image Rotation	
	Intelligent Features	Intelligent Code Stream, Intelligent Video Mask, Intelligent Out-of Focus Detection	
	Protocols	IPv4, TCP/IP, UDP, HTTP, DHCP, RTP/RTCP/RTSP, FTP, UPnP, DDNS, NTP, IGMP, ICMP	
	Compatible Protocol	Onvif	
Port	Audio Port	////////////////////	1CH Audio Input, 1CH Audio Output
	Mobile Surveillance	Support	
General	Working Temperature & Humidity	-20°C ~ 55°C, 20-80% RH (Non-Condensing)	
	Power Supply	DC12V ±10%	
	Dimensions (mm)	42(L) x42(W) x28(D)mm	
	Weight (with Package)	60g	

DIMENSIONS (Unit: mm)

