

IT-3512MP-HD-2MP

ATM HD Network Pinhole Camera



FEATURES

- Support HDTV Full Real-Time HD Picture Quality Transmission
- Support Onvif 2.4X Protocol
- Support Multiple Code Stream, 3D-DNR, Defogging, Motion Detection, WDR, Intelligent Functions
- Support Audio Input / Output, Support TF card, Mobile Surveillance

SPECIFICATIONS

| | | |
|---------|--------------------------------|---|
| Model | Model No. | IT-3512MP-HD-2MP |
| | Type | 2.0 MP ATM HD Network Camera |
| Camera | Image Sensor | 1/2.9" Sony Exmor Progressive Scan CMOS Sensor |
| | Min. Illumination | Color 0.05Lux@F1.2;B/W 0.005Lux@F1.2; |
| | Lens | 3.7mm Pinhole |
| | Electronic Shutter | 1 / 25 ~ 1 / 10000 |
| | DNR | 3D DNR |
| | S/N Ratio | ≥50db (AGC OFF) |
| | WDR | ≥120db |
| | BLC | Support |
| Images | Video Compression | H.265/H.264 /M-JPEG |
| | Code Stream | CBR/ VBR/ LBR |
| | Frame Rate | 1920*1080, 1-25(30)fps ; 1280*720, 1-25(30)fps |
| | Image Setting | Adjustable Image Format, Standard, Bit Rate, Brightness, Contrast, Saturation, Sharpness, White Balance, Image Flip and Mirror; OSD Information Overlay; Image Rotation |
| | Intelligent Features | Intelligent bit stream, intelligent video occlusion, intelligent out of focus detection, intelligent control switch |
| | Protocol | IPv4, TCP/IP, UDP, HTTP, DHCP, RTP/RTCP/RTSP, FTP, UPnP, DDNS, NTP, IGMP, ICMP |
| Port | Compatible Protocol | Onvif |
| | Audio Port | 1CH Audio Input, 1CH Audio Output |
| | TF card | Support |
| General | Mobile Surveillance | Support |
| | Working Temperature & Humidity | -20°C ~ 55°C, 20-80% RH (Non-Condensing) |
| | Power Supply | DC12V ±10% |
| | Dimensions (mm) | 42(L) x42(W) x41(D)mm |
| | Weight (with Package) | 122g |

DIMENSIONS (unit : mm)